


# DIGITUS USB 2.0 connection cable

AK-300110-010-S  
EAN 4016032285793



## USB 2.0 connection cable, type A - micro B M/M, 1.0m, USB 2.0 conform, bl

For connection of external USB devices (with USB micro B socket, e.g. MP3 -player, smart phone or external HDD enclosure) to the USB host (e. g. PC, notebook or USB hub). Data transfer rate up to 480 Mbps (High-Speed).

**Allows a reliable and fast connection of external USB devices with the PC.**

- Data transfer rate up to 480MB/s
- Power supply up to 5V/0,5A and 2.5W
- Copper wire, foil and braid shielding for robustness and reliable connection




### Attributes

- Assortment: USB Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: USB A, plug
- Connector 2: Micro USB B, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- Hoods: molded
- Packaging: Polybag
- USB compliance: USB 2.0
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	13.58	32.00	45.00	25.00	36.00
Packaging Unit Inside	10	0.27	24.00	21.00	3.00	1,512.00
Packaging Unit Single	1	0.03	0.80	9.20	19.60	144,256.00
Net single without Packaging	0	0.03	0.50	10.50	8.50	44,625.00

### More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)