

# DIGITUS® DisplayPort Adapter / Converter

AK-340401-001-S

EAN 4016032289265



**DisplayPort Adapter Cable, Type DP-DVI (24+5) M/F, 0.15m,w/interlock, DP 1.1a, bl**

This digital HD adapter / converter suits for example ideal to connect a notebook or computer with DP interface to a DVI monitor, beamer, LCD/TFT monitor with a DVI cable.

**Perfect for video streams, gaming or extending the workplace**

- Support up to 1080p with 60Hz
- Supports digital full HD and a higher transmission rate by Single Link.
- Copper wire, foil and braid shielding for robustness and reliable connection
- Plug and play, no additional driver needed
- Attention! The DVI socket supports the connection of 24+5 plugs, but only transmits single link 18+1 DVI-D signals in Full HD resolution.
- Supports DisplayPort 1.1
- Bandwidth: 6.75 (2.25 per channel, 225 MHz)
- Color depth: 36bit (12bit per channel)
- Power supply via DisplayPort
- Input: DisplayPort male connector, 20 pin
- Output: DVI female connector, (24+5)
- Resolutions: 480i, 576i, 1080i, 480p, 576p, 720p, 1080p (50 / 60 Hz)
- Operating temperature: 0°C to +45°C
- Operating humidity: 10% to 80% RH (no condensation)

- Storage temperature: -10°C to +80°C
- Storage humidity: 5% to 90% RH (no condensation)
- Power consumption: 300 mW
- Entire cable length: 15 cm
- Color: black

**Attributes**

- Ambalaža: Polybag
- Asortiman: DisplayPort kabele
- AWG: 28
- Blokiranje: Zatvarač na kopču
- DisplayPort standard: DisplayPort 1.1a
- Feritni filter: nema
- HDTV-norma: Full HD
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: DP, utikač
- Konektor 2: DVI-I, (24+5), priključak
- Konektor u boji: crni
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 0.15 m
- AOC - aktivni optički kabel: Ne
- oklop: dvostruki oklop

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
<b>Packaging Unit Carton</b>	200	9.70	38.10	30.20	31.10	35,784.30
<b>Packaging Unit Inside</b>	10	0.49	40.60	40.60	8.10	13,351.70
<b>Packaging Unit Single</b>	1	0.05	20.00	15.00	1.62	486.00
<b>Net single without Packaging</b>	0	0.04	24.50	4.50	1.50	165.38

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)