

DIGITUS® DisplayPort Adapter Cable

AK-340305-020-W
EAN 4016032291466



DisplayPort Adapter Cable, Type mini DP-DVI(24+1) M/M, 2.0m, DP1.1a compatible, wh

This digital HD cable suits for connection of a MacBook, MacBook Air, MacBook Pro, iMac, Mac mini and Mac Pro to a Monitor, Beamer, LCD/TFT Monitor, LED oder Plasma-TV with DVI interface, for example.

Digital Full HD, Dual Link

- Support up to 1080p with 60Hz
- Used chipset PTN3361BB for Full HD resolution 1080p@60Hz
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 10,8 Gbps
- HBR-Version/transfer mode: HBR1 (2,70 Gbit/s per lane)
- HDCP-Version: HDCP 1.3

Attributes

- Ambalaža: Polybag

- Asortiman: DisplayPort kabele
- AWG: 32
- Blokiranje: nema
- DisplayPort standard: DisplayPort 1.1a
- Feritni filter: nema
- HDTV-norma: Full HD
- Kabel u boji: bijeli
- Kapice: ukalupljeno
- Konektor 1: Mini DP, utikač
- Konektor 2: DVI-D, (24+1), utikač
- Konektor u boji: bijeli
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 2 m
- AOC - aktivni optički kabel: Ne
- oklop: dvostruki oklop

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	8.20	50.00	33.00	22.00	36.30
Packaging Unit Inside	1	0.10	3.00	15.00	22.00	990.00
Packaging Unit Single	1	0.10	18.00	15.00	3.50	945.00
Net single without Packaging	0	0.09	14.00	13.00	3.00	546.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com