

DIGITUS® CAT 6A modular couplers, shielded

DN-93905

EAN 4016032291824



CAT6A modular coupler, full shielded RJ45 to RJ45

Corresponds with requirements channel performance Class EA ISO/IEC 11801 for up to 500 MHz

- 2 x RJ-45 female
- Assignment: 1:1
- Shielded version
- Material enclosure: Brass sheet - shining Nickel plated

- Material PCB: FR4, 1.2 mm thickness
- Material contacts: Phosphor bronze
- Contacts coating: Nickel, gold plated 0.6 μ
- Mating cycles: \geq 750
- Operating temperature: -10 °C ~+50 °C

Attributes

- Kategorija: CAT 6A

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	500	10.10	54.50	34.50	13.50	25,383.40
Packaging Unit Inside	50	1.01	25.00	23.00	7.00	4.03
Packaging Unit Single	1	0.02	2.00	7.00	12.00	168.00
Net single without Packaging	0	0.01	1.50	2.50	4.00	15.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com