

DIGITUS Gigabit Media Converter, RJ45 / ST

DN-82110-1
EAN 4016032293118



Gigabit Ethernet Media Converter, Multimode ST connector, 850nm, up to 0.5km

The media converters from DIGITUS® are the ideal solution for the migration of copper and fiber network signals. From now on, you are able to access the fiber technology and transfer network signals over several kilometers without renewing your whole network infrastructure. The huge variety of products fulfil your individual needs. The intuitive operation guarantees a quick and easy installation. Years of experience and a wide range of products lets DIGITUS® become a reliable partner for your network.

The perfect converter solution for various fiber media

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- 10/100/1000Base-TX to 1000Base-SX
- Connectors: 1x RJ45, 1x ST Duplex
- Distance up to 0.5km
- Wavelength: 850nm
- Multimode dual fiber
- Automatic cable detection - auto MDI / MDI-X function
- Auto-negotiation of full- and half-duplex
- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Suitable for 50/125µm and 62.5/125µm multimode fiber cables

- Transmission Power: Minimum -17 dBm, Maximum -12 dBm
- Sensitivity Receiving Power: Minimum -20 dBm
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet, IEEE 802.3z Gigabit Ethernet
- 2MB Data Buffer
- Operating Temperature: 0 to 60°C
- Dimensions (L x W x H): 95mm x 70mm x 26mm
- Weight: 200g
- Standalone Converter with external power supply
- Input Supply Voltage: 5V DC

Attributes

- Connector 1: RJ45
- Connector 2: ST
- Mode: Multimode
- Distance (km): 0.5
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: no
- Ethernet speed: Gigabit

Package contents

- Media Converter
- Quick installation guide
- Power adapter

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	9.00	30.00	27.00	55.00	44.55
Packaging Unit Inside	1	0.45	6.00	21.60	16.10	0.00
Packaging Unit Single	1	0.45	6.00	21.60	16.10	0.00
Net single without Packaging	0	0.19	12.00	7.00	2.60	218.40

More images:



Part Number	Model Code	Speed	Connector	Distance	Medium	Power Supply	Operating Temperature	Product Version
20-00000-01	AS50000001	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-02	AS50000002	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-03	AS50000003	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-04	AS50000004	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-05	AS50000005	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-06	AS50000006	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-07	AS50000007	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-08	AS50000008	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-09	AS50000009	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-10	AS50000010	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-11	AS50000011	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-12	AS50000012	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-13	AS50000013	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-14	AS50000014	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-15	AS50000015	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-16	AS50000016	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-17	AS50000017	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-18	AS50000018	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-19	AS50000019	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-20	AS50000020	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-21	AS50000021	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-22	AS50000022	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-23	AS50000023	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-24	AS50000024	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-25	AS50000025	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-26	AS50000026	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-27	AS50000027	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-28	AS50000028	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-29	AS50000029	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-30	AS50000030	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-31	AS50000031	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-32	AS50000032	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-33	AS50000033	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-34	AS50000034	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-35	AS50000035	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-36	AS50000036	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-37	AS50000037	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-38	AS50000038	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-39	AS50000039	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-40	AS50000040	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-41	AS50000041	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-42	AS50000042	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-43	AS50000043	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-44	AS50000044	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-45	AS50000045	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-46	AS50000046	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-47	AS50000047	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-48	AS50000048	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-49	AS50000049	10/100Mbps	SC Duplex-to-Duplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0
20-00000-50	AS50000050	10/100Mbps	SC Duplex-to-Simplex	2.0km	Fiber	1000mA	0°C to 40°C	1.0

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com