

DIGITUS Gigabit konverter medija, RJ45 / SFP

DN-82130
EAN 4016032293163



KONVERTER DN-82130 SC/RJ45 ZA SFP 10/100/1000-D SFP Open Slot, without SFP Module

Konverteri medija iz DIGITUS® ponude idealno su rješenje za prijelaz signala između tehnologija bakra i optike. Od sada pa nadalje pristupiti možete tehnologiji optike i poslati komunikacijske signale na udaljenostima od nekoliko kilometara bez obnavljanja Vaše cjelokupne komunikacijske infrastrukture. Široka raznolikost ponude ispunjava sve Vaše potrebe. Intuitivni redoslijed operacija garantira brzu i jednostavnu instalaciju. DIGITUS® je zahvaljujući dugogodišnjem iskustvu i širokom ponudom postao pouzdani partner za Vaše mreže.

The perfect converter solution for various fiber media

- Transforms wire based network media to fiber optic
- High quality and excellent reliability
- Connectors: 1x RJ45, 1x SFP
- Distance up to 80km
- Automatic cable detection - auto MDI / MDI-X function
- Auto-negotiation of full- and half-duplex
- Diagnostic and monitoring LEDs for the status of power, link and act of the ports
- Supported Standards: IEEE 802.3 Ethernet, IEEE 802.3u Fast Ethernet, IEEE 802.3z Gigabit Ethernet

- 2MB Data Buffer
- Operating Temperature: 0 to 60°C
- Dimensions (L x W x H): 95mm x 70mm x 26mm
- Weight: 200g
- Standalone Converter with external power supply
- Input Supply Voltage: 5V DC
- Exclusive SFP Module
- Supports both 155M SFP and 1G SFP

Attributes

- Konektor 1: RJ45
- Konektor 2: SFP
- Mod: Bakar
- Udaljenost (km): Ovisno o modulu
- Industrijska uporaba: Ne
- Način emitiranja: Ovisno o modulu
- PoE injektor: Ne
- Ethernet brzina: Gigabit

Package contents

- Media Converter
- Quick installation guide
- Power adapter

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	9.00	30.00	27.00	55.00	44.55
Packaging Unit Inside	1	0.45	5.50	13.00	24.00	1.72
Packaging Unit Single	1	0.45	5.50	13.00	24.00	1.72
Net single without Packaging	0	0.00	2.60	7.00	9.50	172.90

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.
 ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com