


# DIGITUS Datatransfer extension cable, D-Sub25/M - D-Sub25/F

AK-610201-030-E  
EAN 4016032301202



**Datatransfer extension cable, D-Sub25 M/F, 3.0m, serial/parallel, molded, be**

Datatransfer extension cable, D-Sub25,M/F, 3.0m, serial/parallel, molded, be

**Enables a save and stable connection**

**Attributes**

- Assignment: 1:1
- Assortment: Serial and Parallel Adapters
- AWG: 28

- Cable type: 25-wire
- Color cable: beige
- Color connector: beige
- Connector 1: DSUB, 25-pin, plug
- Connector 2: DSUB, 25-pin, jack
- Connector surface: nickel-plated
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 3 m
- Shielding: single shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	40	16.40	35.00	22.00	38.00	29.26
Packaging Unit Inside	10	4.10	36.00	36.00	13.00	16,848.00
Packaging Unit Single	1	0.41	27.00	15.00	5.00	2,025.00
Net single without Packaging	0	0.30	15.50	15.00	4.50	0.00

**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)