

DIGITUS® mini GBIC (SFP) Module, 1.25 Gbps, 20km

DN-81003

EAN 4016032305682



1.25 Gbps SFP Module, Singlemode, BiDi LC Simplex, Tx1310nm/Rx1550nm, up to 20km

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik , ENTERASYS, RIVERSTONE , Unifi, Ubiquiti, ZyXEL, ZTE
- Bidirectional WDM Module - Only one fiber is needed
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Simplex
- Wavelength: Tx 1310nm / Rx 1550nm
- Transmission Power: Minimum -5 dBm, Maximum 0 dBm
- Sensitivity receiving power: minimum -24 dBm
- For a Distance of up to 20km
- Suitable for OM3/OM4 Singlemode Fiber Cables
- Safe fast-locking mechanism
- 3.3V power supply
- Suitable Module for Opposite Side: DN-81004
- Operating temperature: 0 °C ~ 70 °C

Attributes

- Mode: Singlemode
- Connector: LC
- Distance (km): 20
- Wavelength: 1310/1550 nm
- DDM Support: no
- Broadcasting Mode: Bidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79.03
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4.20
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

SFP Modules						
Part Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature
Fast Ethernet						
DS-4101	10/100/1000	10/100/1000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4102	10/100/1000	10/100/1000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4103	10/100/1000	10/100/1000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4104	10/100/1000	10/100/1000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
10GbE						
DS-4105	10/100/1000/10000	10/100/1000/10000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4106	10/100/1000/10000	10/100/1000/10000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4107	10/100/1000/10000	10/100/1000/10000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4108	10/100/1000/10000	10/100/1000/10000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4109	10/100/1000/10000	10/100/1000/10000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4110	10/100/1000/10000	10/100/1000/10000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
100GbE						
DS-4111	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4112	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4113	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4114	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4115	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4116	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4117	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4118	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C
DS-4119	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1310nm	0 to 70°C
DS-4120	10/100/1000/10000/100000	10/100/1000/10000/100000	10km	LC Duplex Small Form-factor Pluggable	1550nm	0 to 70°C



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com