

DIGITUS USB 3.0 IDE & SATA Cable

DA-70325 EAN 4016032306481





DA-70325 DIGITUS USB 3.0 IDE & SATA Cable Power Supply (12V/2A) included

USB 3.0 adapter cable for fast and easy HDD connections - no external enclosure needed. Use any 2.5 / 3.5 IDE hard drive or SATA hard disk as an additional external hard drive. Ideal for service, maintenance, hassle-free temporary HDD access, e.g. for data backups and restore purposes.

Convert your SATA/ IDE hard drive into an external USB drive - ideal for backup and service!

- · Capacity: up to 8 TB
- Supports 2.5/3.5 IDE and SATA HDDs
- Supported data transfer rates: Super-Speed (5Gbps), High-Speed (480Mbps), Full-Speed (12Mbps) and Low-Speed (1.5Mbps)

- Supports SATA 1.5 Gbps /3.0 Gbps speed negotiation
- Compliant to Universal Serial Bus 3.0 specification, downwards compatible to USB 2.0, 1.1 specification
- Compliance with USB Mass Storage Class
- Plug & play and hot-swappable
- incl. power supply 12V/2A
- Compliant to Serial ATA2.6

Package contents

- USB 3.0 IDE & SATA cable
- 3.5" to 2.5" adapter
- 4Pin power cable
- Power supply 12V / 2A

| Logistics | | | | | | |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 30 | 12.00 | 50.50 | 32.30 | 47.60 | 0.00 |
| Packaging Unit Inside | 1 | 0.40 | 23.50 | 15.00 | 6.00 | 2,115.00 |
| Packaging Unit Single | 1 | 0.40 | 23.50 | 15.00 | 6.00 | 2,115.00 |
| Net single without Packaging | 0 | 92.00 | 10.50 | 2.00 | 3.50 | 73.50 |

More images:











Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- · Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com