

DIGITUS CAT 6 S/FTP patch cord

DK-1644-0025/WH EAN 4016032321521





CAT 6 S-FTP patch cord, Cu, LSZH AWG 27/7, length 0.25 m, color white

The DIGITUS® Category 6 Class E patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6 cabling. The performance is tested up to 250 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6, because of the transparent red colored connector.

Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- · Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 6
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: 0.25 m
- · Color: white
- Jacket: LSOH Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair

| Logistics | | | | | | |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|--------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 250 | 5.80 | 36.00 | 36.00 | 22.00 | 28.51 |
| Packaging Unit Inside | 10 | 0.23 | 6.00 | 20.00 | 25.00 | 3.00 |
| Packaging Unit Single | 1 | 0.02 | 1.00 | 10.00 | 20.00 | 200.00 |
| Net single without Packaging | 0 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

More images:









