

DIGITUS Flat telephone installation cable

AK-460702-100-S EAN 4016032329879





8-wire flat telephone installation cable for TAE-or modular (RJ-xx) plug systems.

- · Modular cable unshielded, AWG26
- Flat cable with 4, 6, or 8 wires (D-shape)
- 100m per reel



- Color: black with color coded wires
- · Other lengths per reel, versions, and colors on request

Attributes

- Assortment: Telecommunication Cables
- Length: 100 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	4	12.78	36.00	18.00	34.00	22,032.00
Packaging Unit Inside	1	3,195.00	15.50	17.00	17.00	0.00
Packaging Unit Single	1	3,195.00	15.50	17.00	17.00	0.00
Net single without Packaging	0	2.97	15.50	17.00	17.00	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

 $\hbox{EU based economic operator ensuring the product complies with the required regulations.}\\$

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com