DIGITUS® Modular Plug for Round Cable, CAT 6A, shielded, Pass through connector

AK-219604

EAN 4016032380627



CAT 6A Modular Plug, 8P8C, shielded for solid wire AWG 22-23, pass through

These modular plugs can be used to establish quick and simple connections.

- Crimping tool – DN-94025 (Multi Modular Crimping Tool Pass through connectors)
- Layout performance: CAT 6A, 10GBase-T
- Area of application: Patch cable assembly
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- UL certified
- Technical properties:
- Mating cycles female: > 750 acc. to ISO/IEC 11801, IEC 60603-7-5
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.6 ☒ gold-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: ☒ 30 N
- Diameter Cu-Conductor: AWG (23/1... 22/1)
- Operating temperature: -40 °C to +80 °C
- Current carrying capacity: 1A -1.5A at 50 °C

Attributes

- Kategorija: CAT 6A

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3	14.34	37.00	51.00	33.00	62.27
Packaging Unit Inside	100	0.40	23.00	33.00	2.00	1.52
Packaging Unit Single	1	0.00	1.00	2.00	0.50	1.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany

https://www.assmann.com
info@assmann.com