

DIGITUS Wall Mounting Cabinets - Flush Mount

DN-19 WM-FLSH-127
EAN 4016032383208



Flush mount wall mounting cabinet, tilt-out 778x628x127 mm, 2U, color grey (RAL 7035)

The flush- & surface mount Wall Mounting Cabinets allow a vertical, secure mounting for example for small sound equipments, networks, DVR, paging- and patching applications. The front door is able to swing-out. The Wall Mounting Cabinets are available in two different versions: With 2U or 4U possibilities for rack mounting.

Slim design with swing-out front door

- 1.0 - 1.5 mm strong steel sheet
- 2U usable space inside
- Pre-punched cable entry in the middle of the rear side (216x216 mm)
- Punched out cable entries with plastic cover on the rear side, as well as top and bottom (145x70 mm)
- Lockable front door with air ventilation units
- Front door is able to swing-out and is equipped with two stop functions (first stop at 25°, second stop at 115°)

- Several cable fixing points for a neat cable management
- Dimensions inner area (HxWxD): 750x600x116 mm
- Max. equipment mounting height inside: 402 mm
- Cabinet depth for flush wall mounting: 117 mm
- Cabinet type: Wall mounting cabinet, home automation
- Color: light grey, RAL 7035
- Depth: 127 mm
- Front door: Steel door, closed, single opening
- Load capacity: 100 kg
- Side panels: Both sides
- Units: 2
- Width: 628 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Earthing wire set

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	17.00	13.70	63.80	78.80	68,875.90
Packaging Unit Inside	1	17.00	13.70	63.80	78.80	68,875.90
Packaging Unit Single	1	17.00	13.70	63.80	78.80	68,875.90
Net single without Packaging	0	15.00	12.70	62.80	77.80	62,050.20

More images:

