

# **DIGITUS DisplayPort Adapter / Converter**

DB-340409-001-S EAN 4016032383222





# DisplayPort Adapter Cable, Type DP-DVI (24+5) M/F, 0.15m,w/interlock, Full HD, DP 1.1a, bl

This digital HD adapter / converter suits for example ideal to connect a notebook or computer with DP interface to a DVI monitor, beamer, LCD/TFT monitor with a DVI cable.

# Clear and sharp display - Full HD resolution

- Full HD, Dual-Link
- Max. supported Video Resolution: 1920 x 1080 p with 60 Hz
- Maximal bandwidth: 10,8 Gbps
- HBR-Version/transfer mode: HBR1 (2,70 Gbit/s per lane)
- HDCP-Version: HDCP 1.3

## Attributes

- Assortment: DisplayPort Cables
- Color cable: black
- · Color connector: black
- Connector 1: DP, plug
- Connector 2: DVI-I, (24+5), jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- · Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- · Interlock: Snap fastener
- Length: 0.15 m
- AOC Active Optical Cable: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	6.00	52.00	29.00	39.00	58,812.00
Packaging Unit Inside	20	1.50	27.00	27.00	17.00	12,393.00
Packaging Unit Single	1	75.00	2.30	7.50	23.50	405,375.00
Net single without Packaging	0	0.04	2.00	6.00	20.00	240.00

### More images:













#### Safety notes

- $\bullet \quad \text{When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.}\\$
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com