

DIGITUS HDMI Splitter, 1x8

DS-43302**EAN 4016032387176****HDMI Splitter, 8-port, 1080p, 3D, High Speed 2.25 Ghz/225 MHz, metal housing, black**

The Digitus 8-Port HDMI Splitter allows you to distribute video signals to up to eight playback devices (TVs, displays, monitors, projectors, etc.). It supports video resolutions of up to 1080p (Full HD). It provides the ideal solution for professional applications, such as video wall presentations or product launches (offices/business spaces, trade fair exhibits, display windows, waiting rooms, restaurants/café, etc.). The splitter can be cascaded to one level and up to eight additional HDMI 8-Port Splitters can be connected in order to display the signal on a maximum of 64 playback devices.

Splitting of HDMI video signals to up to eight output devices (TVs, monitors, displays)

- Splitting of HDMI video signals to up to eight playback devices
- HDMI connections: 1x input, 8x outputs
- Video resolution: 1920 x 1200, 1080p
- Supports high-speed HDMI
- Supports HDCP (HDCP 1.0/1.1/1.2)
- Supports compressed audio formats, for example, DTS Digital, Dolby Digital (including DTS-HD and Dolby TrueHD)
- Cascadable (one level) to up to 64 HDMI ports (playback devices)

- Video resolution: 1920 x 1080. Suitable for 480i, 576i, 1080i, 480p, 576p, 720p, 1080p.
- Supports all 3D formats, including 1080p @ 24 Hz, 720p @ 60 Hz/50 Hz
- Bandwidth of 225 MHz/2.25 Gbps per channel (6.75 Gbps across all channels)
- Supports uncompressed audio formats (LPCM, etc.)
- Supports Deep Color: 12 bits per channel
- Status LEDs (connection status)
- External power supply unit (5V/3A)
- Dimensions: L 11.1 x W 25.8 x D 2.7 cm
- Weight: 730 g

Attributes

- HDTV Resolution max.: 1920 x 1200 Pixel, 60Hz
- HDTV Standard: Full HD
- Number of ports: 8
- Signal input: HDMI

Package contents

- HDMI Splitter, 1x8
- Operating instructions
- External power supply unit (5V/3A)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	22.20	59.60	57.50	25.20	0.00
Packaging Unit Inside	1	1.11	24.00	29.50	5.50	3,894.00
Packaging Unit Single	1	1.11	24.00	29.50	5.50	3,894.00
Net single without Packaging	0	0.73	11.10	25.80	2.70	773,226.00

More images:



Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com