

DIGITUS USB 3.1 Type-C™ - SATA 3 adapter cable for 2.5" SSDs/HDDs

DA-70327

EAN 4016032390565



SATA Adapter Cable USB Type-C to SATA III, chipset: NS1068X, 5Gbps

The Digitus USB 3.1 Type-C™ - SATA 3 adapter cable enables quick and easy access to your 2.5" SATA III SSDs/HDDs via the USB 3.1 Type-C™ port on your PCs/notebooks. Thanks to the USB 3.1 (Gen 1) interface, extremely fast data transfer rates of up to 6 Gbit/s are ensured. This also provides UASP support for improved performance. It does not require additional power supply, the power supply is ensured via the USB port.

Faster and easier access to your 2.5" SATA III SSDs/HDDs via the USB 3.1 Type-C™ port on your PCs/notebooks

- Faster and easier access to your 2.5" SATA III SSDs/HDDs via the USB 3.1 Type-C™ port on your PCs/notebooks
- Connector 1: USB 3.1 Type-C™
- Connector 2: SATA (22 pin)
- Supports 2.5" SATA I-III SSDs/HDDs
- USB 3.1 (Gen 1) - data transfer rate of up to max. 5 Gbit/s

- Supports UASP (USB Attached SCSI Protocol)
- SATA III - data transfer rate of up to max. 6 Gbit/s
- Support capacity: up to 5 TB
- Chipset: NS1068X
- Supports hot-plugging and is plug & play capable
- Power supply via USB port
- Supports: Win 10 (64 bit), 10, 8.1 (64 bit), 8.1, 8 (64 bit), 8, 7 (64 bit), 7, Mac OS 10.11 or higher, Linux Kernel 3.19 or higher, Google Chrome OS
- Cable length: 35 cm
- Weight: 20 g
- Color: Black

Attributes

- USB-C Products: yes

Package contents

- USB 3.1 Type-C™ - SATA 3 adapter cable for 2.5" SSDs/HDDs
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	10.90	38.10	30.20	31.10	0.00
Packaging Unit Inside	1	0.05	8.00	12.00	1.50	144.00
Packaging Unit Single	1	0.05	8.00	12.00	1.30	124.80
Net single without Packaging	0	19.00	21.50	4.50	1.10	106,425.00

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com