

DIGITUS Oklopljeni RJ45 mikroutikač za nabacivanje na gradilištu

DN-93631
EAN 4016032392231



AMO 8/8 M-KON. C6A, FTP, 10GBit, field assembly dust cap, TIA 568-A,B,Profinet

DIGITUS® Kat. 6A RJ45 mikroutikač za nabacivanje na gradilištu moderan je i visokokvalitetan mikroutikač koji karakterizira uvijek jednostavninu i brzu primjenu te pouzdanost. Brza montaža u 60 s bez uporabe specijalnih alata te visoka fleksibilnost savršeno je rješenje za bilo koje gradilište. Prikidan je za uporabu na svim mrežama do 10 Gigabit Ethernet. Ovaj inovativni RJ45 mikroutikač je logična posljedica zadovoljnog kupca uslijed njegove brze montaže, ušteda kod instalacije, popravaka i održavanja. Zašto komplikirati stvari koje mogu biti tako jednostavne? Provjerite sami!

- Preassembled protection cap
- Robust zinc diecast housing
- 360° cable screen connection for enhanced EMI protection
- Can be assembled in 60 seconds without any special tools
- Optimised for the field, including demanding applications
- Secure transmission even with outside interference
- Ideal for network repairs, special length and extensions
- Cross sections AWG 27/7-22/7, AWG 24/1-22/1

- Insulation: 0.85 - 1.6 mm
- Cable diameter: 5.0-9.0 mm
- Dimensions (W x H x D): 12.5 x 13.0 x 45.0 mm
- Weight: 78 g
- --Climatic Characteristics:
- Operating temperature: -40 °C to +80 °C
- --Electrical Characteristics:
- Current carrying capacity at 50°C: 1 A
- PoE+ acc to IEEE 802.3at: Adequate for Power over Ethernet+
- --Standards:
- Gigabit Ethernet acc. to IEEE 802.3
- 10 Gigabit Ethernet acc. to IEEE 802.3an: Adequate for 10 Gigabit Ethernet

Package contents

- 1x plug with dust cap
- 1x sleeve with kink protection and strain relieve
- 1x wire manager with wiring instruction
- 1x cable tie
- 1x mounting instruction

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	250	9.44	54.00	31.00	28.00	46.87
Packaging Unit Inside	1	0.04	12.50	4.50	2.50	140.63
Packaging Unit Single	1	0.04	12.50	4.50	2.50	140.63
Net single without Packaging	0	0.04	12.50	4.50	2.50	140.63

More images:

