

DIGITUS CAT 6 Industrial Keystone Module, shielded

DN-IND-C6-KJ
EAN 4016032429609



CAT 6 industrial keystone jack, IP67, shielded with dust cap

CAT 6 industrial keystone jack, IP67, shielded,with dust cap

Best performance and link quality for your network. Ideal for industrial applications.

- Main body & dust cap: PBT+GF, UL94V-0
- Module housing, contact holder & IDC plastic: PC, UL94V
- Module contacts: Phosphor bronze, 50 µ gold plated
- IDC terminals: Phosphor bronze, tin over nickel undercoat
- Insertion life: 750 mating cycles with FCC compliant 8P plug
- Contact force: 100 g with FCC compliant 8P plug
- Plug retention force: 11 LBF min.

- Durability: 200 termination cycles
- Contact compability: Accomodates 22 to 24 AWG solid
- Operating temperature range: -10 °C up to +60 °C
- Storage temperature range: -40 °C up to + 68 °C
- Humidity: 10%~90% RH
- Insulation resistance: 500 MΩ
- Dielectric withstanding voltage: 1000 V AC
- DC current rating: 1.5 Amps.
- DC resistance: 0.1 Ω
- Contact resistance: 20m Ω
- Contact resistance: 20m Ω

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	1.68	17.00	30.00	10.00	5.10
Packaging Unit Inside	1	0.03	3.00	6.50	2.00	39.00
Packaging Unit Single	1	0.03	3.00	6.50	2.00	39.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:

