

# DIGITUS® DisplayPort Adapter Cable, DP - HDMI type A

AK-340303-030-S

EAN 4016032438601



**DisplayPort Adapter Cable, Type DP - HDMI A M/M, 3.0m, w/lock, 4K@60Hz, DP 1.4, HDMI 2.0, bi**

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with HDMI interface.

**Avoid the hassle of adapters, with a plug-and-play adapter cable which doesn't require external power**

- Support of HDMI 2.0 Features
- Support up to 4K/2K with 60Hz
- Support of 3D with 1080p resolution
- Support of HDCP and DPCP
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)

**Attributes**

- Ambalaža: Polybag
- Asortiman: DisplayPort kabele
- AWG: 28
- Blokiranje: Zatvarač na kopču
- DisplayPort standard: DisplayPort 1.4
- Feritni filter: nema
- HDTV-norma: Ultra HD 4K
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: DP, utikač
- Konektor 2: HDMI tip A, utikač
- Konektor u boji: crni
- Materijal žice: CU
- Površina konektora: poniklano
- Duljina: 3 m
- AOC - aktivni optički kabel: Ne
- oklop: trostruki oklop

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	40	9.70	25.00	35.00	55.00	48.13
Packaging Unit Inside	10	2.43	10.00	24.00	38.00	9.12
Packaging Unit Single	1	0.24	3.00	18.00	18.00	972.00
Net single without Packaging	0	0.00	2.00	17.00	17.00	578.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)