

DIGITUS® CAT 6A U/FTP installation cable, 100 m, simplex, B2ca

DK-1626-A-VH-1

EAN 4016032441823



CAT 6A U-FTP installation cable, 500 MHz B2ca (EN 50575), AWG 23/1, 100 m paper box,

The Digitus® Cat.6A U/FTP installation cable is characterized by the following cable construction 4x2x AWG23/1 and reaches a transmission frequency up to 500 MHz. The halogen free cable jacket is conform to the standard IEC 60332-1, FRNC-B, LSZH-1 and CPR Euro class B2ca. The cable is suitable for building structured cabling in the secondary and tertiary area. Compliant with the following standards ISO/IEC 11801, DIN EN 50173, DIN EN 50288-10-1.

Future-oriented standards and high-end quality for your network.

- Physical properties:
- Conductor: Bare annealed copper, solid AWG 23/1
- System/s of AVCP: AVCP 3
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Individual pair shielding: Aluminum foil, providing 100 % coverage
- Overall shielding: None, with drain wire
- Outer sheath: Eca to B2ca acc. to EN 50575; LSZH
- Outer sheath color: Light blue (RAL 5012)
- Mechanical properties:
- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +60 °C
- Operating temperature range: -20 °C up to +75 °C



- Installation temperature range: 0 °C up to +50 °C
- Overall diameter Simplex (nominal): 7.0 (Eca); 7,2 mm (Dca); 7,6 mm (Cca); 7,6 mm (B2ca)
- Weight (kg/km): 56 kg (Eca); 57 kg (Dca); 58 kg (Cca); 58 kg (B2ca)
- Electrical properties:
- Impedance: 100±15 Ohm @ 4 - 100MHz; 100±25 Ohm @100-500 MHz
- Capacitance: 45 pF/m nominal @ 1KHz
- Capacitance unbalance (pair-ground): 1.6 pF/m max. @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC loop resistance: 190 Ohm/km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: CA-Type 2
- Signal propagation delay: 450 nS/100 m max.
- Propagation delay: 15 nS/100 m max.
- Separating class: "c" acc. to EN 50174-2
- NVP: 70%

Attributes

- Asortiman: Instalacijski kabele s upredenim paricama
- Kategorija: CAT 6A
- Oklop: U-FTP, parovi u metalnoj foliji
- CPR: B2ca
- Duljina: 100 m
- Boja: svijetlo plavi
- Kapica: LSOH
- Struktura: 4 x 2 AWG 23/1, kruto upletena parica

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



DIGITUS

AWG 23/1 500 MHz 10 Gbit Ethernet CAT 6A E_{ca}


20°/75° LSZH CPR class

CAT 6A U/FTP Installation Cable, 100m, Simplex, E_{ca}

DIGITUS

EN Normen	Bestandteile	Leistungsleistung (dB/100m)	Spezifikationen	Zusätzliche Informationen
B2ca	Sehr hoch	1+	<ul style="list-style-type: none"> • Symmetrisch • Regelmäßige Abschirmung • Hohe Leiterqualität • Hohe Leiterqualität 	<ul style="list-style-type: none"> • 100% Qualitätsprüfung • 100% Qualitätsprüfung • 100% Qualitätsprüfung
C _{ca}	Hoch			
D _{ca}	Mittel	3	<ul style="list-style-type: none"> • Symmetrisch • Regelmäßige Abschirmung 	<ul style="list-style-type: none"> • 100% Qualitätsprüfung • 100% Qualitätsprüfung
E _{ca}	Gering			<ul style="list-style-type: none"> • 100% Qualitätsprüfung • 100% Qualitätsprüfung

Produktcode: C_{ca} s1a d1 a1



Certificate No. 48864-21 **Zertifikat** No. 48864-21

Category 6e Kategorie 6e

GHMT Type Approval

Intertek

ETL Verified Certificate of Conformance Number: 194220903P-011

Model: CAT 6A U/FTP Installation Cable, 100m, Simplex, E_{ca}

Product Code: C_{ca} s1a d1 a1

DK-1623-A-VH-1 // CAT 6e U/FTP Installation Cable, 100m, Simplex, E_{ca}

Anwendungsbeispiel
Example of use

DK-1623-A-VH-1 // CAT 6e U/FTP Installation Cable, 100m, Simplex, E_{ca}

Kabelquerschnitt
Cable cross section

DIGITUS

Leistungsparameter / Performance Properties

PROB.	AT	EXT.	PL-NEZ.	AKN.	PL-NEZ.	HL.	EL-EXT.	PRE-EXT.
10	1.1	20	10	10.0	10.1	20	10	10
10	1.1	20	10	10.0	10.1	20	10	10
10	1.1	20	10	10.0	10.1	20	10	10
10	1.1	20	10	10.0	10.1	20	10	10
10	1.1	20	10	10.0	10.1	20	10	10

DIGITUS

Produktdaten / Product Information	Physikalische Spezifikationen / Physical Properties
Produktname: CAT 6A U/FTP Installation Cable, 100m, Simplex, E _{ca} Artikelnummer: DK-1623-A-VH-1 Hersteller: Digitus Material: PVC, LSZH, 23 AWG, 100m, Simplex, E _{ca}	Leitungsleistung: 10 Gbit Ethernet Leitungsleistung (dB/100m): 1+ Leitungsleistung (dB/100m): 3 Leitungsleistung (dB/100m): 3

Safety notes

- Data cables must not be bent, stretched or twisted excessively. Sharp bends can damage the cable sheath and lead to failures or short circuits.
- Installation only by trained specialists.
- Installation only in dry rooms.
- The data cable must not be in direct contact with other electrical cables or high-voltage sources in order to avoid electromagnetic interference.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com