

# DIGITUS DisplayPort Connection Cable

**AK-340106-020-S**  
**EAN 4016032450313**



## DisplayPort connection cable, DP M/M, 2.0m, w/interlock, Ultra HD 8K,

With this cable standard, this DisplayPort cable supports all of today's requirements - from the playback of high-resolution UHD 8K content through 8-channel audio transmission to the support of HDCP and DPCP encryptions. Mirror your laptop desktop on a large monitor or extend your desktop with another DisplayPort display. This high-quality cable allows rapid data transfer without jerking, even in demanding graphics applications or games. Gold-plated contacts and double shielding of the cable ensure maximum conductivity and trouble-free transmission.

### Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Transfer rate: up to 32.4 GBit/s
- Supports up to 4K/2K@120Hz (Ultra HD ) resolution
- Supports up to 5K@60Hz (Ultra HD) resolutions
- Supports up to 8K@30Hz (Ultra HD) resolutions

- Supported video resolution: 7680 x 4320 dpi; 5120 x 2880 dpi; 3840 x 2160 dpi
- Color depth: 24bit RGB
- Supports 1-8 audio channels for audio transmission
- Audio sampling frequencies: 32-192 kHz with max. bit rate of 4,608 kB/s
- Supports HDCP and DPCP
- Plug & Play installation
- DisplayPort version: 1.3 / 1.4

### Attributes

- DisplayPort standard: DisplayPort 1.4
- HDTV rezolucija maks.: 7680 × 4320 piksela, 60 Hz
- HDTV-norma: Ultra HD 8K
- Kabel u boji: crni
- Konektor 1: DP, utikač
- Konektor 2: DP, utikač
- Površina konektora: poniklano
- Duljina: 2 m
- AOC - aktivni optički kabel: Ne

## Logistics

|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm <sup>3</sup> |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------------|
| Packaging Unit Carton        | 50              | 7.75           | 33.00         | 44.00         | 22.00          | 31.94           |
| Packaging Unit Inside        | 5               | 0.78           | 28.00         | 36.00         | 25.00          | 25.20           |
| Packaging Unit Single        | 1               | 0.16           | 3.00          | 17.00         | 25.00          | 1.28            |
| Net single without Packaging | 0               | 0.16           | 3.00          | 15.00         | 14.00          | 630.00          |

### More images:



### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)