

USB Type-C™ - HDMI + VGA Adapter

DA-70858

EAN 4016032451525



USB Type C to HDMI + VGA Adapter 4K/30Hz / Full HD 1080p, black

The USB Type-C™ - HDMI + VGA video adapter extends your USB-C™ device with two video ports (HDMI and VGA). Connect an additional TV set or monitor to your laptop or hold a presentation with a projector. The highest possible resolution is UHD (4K/30Hz). You can use an additional monitor provided two monitors are connected, with the HDMI port having the priority. The video adapter is suitable for all operating systems: Windows, Mac, Google Chrome.

Extends your USB-C™ device with two video interfaces (HDMI and VGA)

- Connection 1: USB-C™ plug
- Connection 2: HDMI socket
- Connection 3: VGA socket
- Video signal playback on one TV/monitor, if two TVs/monitors are connected at the same time (priority: 1 HDMI, 2 VGA)
- Extends your USB-C™ device with two video interfaces (HDMI and VGA)
- 1x HDMI (UHD, 4K/30Hz)
- 1 x VGA (Full HD)
- USB-C™ version: USB 3.1 (Gen. 1)
- Corresponds to the VESA DisplayPort Alternate Mode
- Chipset: VL100/IT6562FN
- Cable length: 11.0 cm
- Color: Black

- Dimensions: L 18.0 x W 4.0 x H 1.4 cm
- Weight: 35 g
- Not all USB-C™ ports support all functions of USB Type-C™ standards. Make sure that the USB-C™ port of your laptop supports the DisplayPort Alternate Mode (DP Alt-mode).
- The video output capability depends on the graphics card of your laptop and the connected monitor. Some screens also have a limited resolution.

Attributes

- Housing: Aluminum
- LAN connector (RJ45): no
- Resolution max.: 4096 x 2160 Pixel, 30Hz
- Card reader: no
- Number of audio ports: 0
- Number of display ports: 2
- Number of network ports: 0
- Number of USB A ports: 0
- Number of USB-C ports: 1
- Number of video ports: 2
- USB-C Products: yes
- Video connection ports: HDMI, VGA

Package contents

- USB Type-C™ - HDMI + VGA Adapter
- QIG (quick installation guide)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	80	8.00	50.00	34.00	30.00	51.00
Packaging Unit Inside	1	0.10	23.50	7.50	2.30	405.38
Packaging Unit Single	1	0.10	23.50	7.50	2.30	405.38
Net single without Packaging	0	0.04	6.00	4.00	1.40	33.60

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.