

DIGITUS HDMI Ultra High Speed connection cable, type A

AK-330124-020-S
EAN 4016032454328



HDMI Ultra High Speed connection cable, type A M/M, 2.0m, w/Ethernet, UHD 8K 60p, gold, bl

With this cable standard, the ultra high speed HDMI cable supports all current requirements – from the transmission of high-resolution UHD 8K content, two-way audio transmission (ARC) and control of HDMI devices via CEC. Internet applications can also be used without the additional need to connect an Ethernet cable (HEC). Lip Sync means that delayed lip movement is a thing of the past. This cable can also be used to transmit up to 32 audio channels and enjoy image output in 21:9 CinemaScope format. Get more out of your Blu-ray player, gaming console or HD streaming portal. Gold-plated contacts and triple shielding of the cable ensure maximum conductivity and interference-free transmission. Also supports 4K 3D in 50/60 Hz.

This cable already meets the requirements of future high-definition devices (TV, beamer, monitor) of the next generation, with higher resolutions, higher data rates and higher frame refresh rates.

- Supports up to 8K with 60Hz
- Support for 4K 3D with 50/60Hz
- Support of 14 and 16 bit color depth
- Support for HDR (High Dynamic Range)
- Supports Audio Return Channel (ARC)
- Supports Consumer Electronic Control (CEC)
- Supports lip-sync (audio/video synchronization)

- Dolby TrueHD capable
- Multi stream audio/video support
- 21:9 Cinemascope support
- 32 channel audio support
- With Ethernet channel (HEC)
- Supports 120 Hz at 1920 x 1080p resolution
- Supports 4K 50/60 Hz
- Supports 1080p 3D HFR
- Supports Deep Color 30bit
- Supports DTS-HD master audio bitstream
- Supports Super Audio CD (DSD)
- Supports DVD-Audio
- Supports Blu-Ray Disc and HD-DVD audio and video
- HDMI version: 2.1
- HDMI standard: Ultra High Speed HDMI

Attributes

- HDMI-norma: Ultra brzi HDMI
- HDTV rezolucija maks.: 7680 × 4320 piksela, 60 Hz
- HDTV-norma: Ultra HD 8K
- Konektor 1: HDMI tip A, utikač
- Konektor 2: HDMI tip A, utikač
- Površina konektora: pozlaćeno
- Duljina: 2 m
- AOC - aktivni optički kabel: Ne

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	50	8.20	44.00	33.00	22.00	31,944.00
Packaging Unit Inside	10	1.64	42.00	30.00	27.00	34.02
Packaging Unit Single	1	164.00	17.00	3.00	15.00	765.00
Net single without Packaging	0	142.00	15.00	3.00	14.00	630.00

More images:**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable.
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com