

DIGITUS USB Type-C™ Gigabit Ethernet adapter with Power Delivery support

DN-3027 EAN 4016032458043





USB-Type-C Gigabit Ethernet Adapter + PD with power delivery function

The USB Type-C™ Gigabit Ethernet adapter allows you to extend your laptop to a network connection and reach speeds of up to 1000 Mbps. No need to install drivers with a CD - thanks to the virtual drive, you can just plug it in and get started. Power is also supplied via a USB-C™ port with Power Delivery (PD) 2.0, which also charges the connected device. The adapter is compatible with Windows, macOS, Google Chrome and all other systems that are compatible with USB-C™. The adapter is an ideal travel companion thanks to its compact dimensions

Extend your laptop with USB-C $^{\rm IM}$ port to a Gigabit network connection with Power Delivery support

- Supports USB Type-C™ connections
- Gigabit data transfer of up to 1000 Mbps.
- RJ45 Ethernet connection with LED function display 10/100/1000 Mbps

- Plug and play directly install the driver from the device (virtual CD drive)
- Provides a USB-C™ port with Power Delivery (PD) 2.0 to charge your mobile device
- Full Duplex data flow control (10M/100M/1G) Auto-Negotiation
- Supports patch cables and crossover cables, automatic recognition and changeover
- Operation temperature: 0°C to +45°C
- Operating humidity: 10% to 85% (non-condensing)
- Powered via USB-C™ (4.75 ~ 5.25 V)
- 1x USB-C[™] port Power Delivery (PD) 2.0 (max. 60 W, 20 V/3 A) + data transfer (max. 1 Gbps)
- Material: Plastic case
- Dimensions: L 4.1 x W 4.1 x 1.5 cm
- Weight: 23 g

Package contents

- 1x USB Type-C™ Gigabit Ethernet adapter with Power Delivery support
- 1x Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	7.50	40.00	34.00	30.00	40.80
Packaging Unit Inside	20	1.88	24.00	28.00	16.00	10.75
Packaging Unit Single	1	0.09	7.50	23.50	2.30	405.38
Net single without Packaging	0	0.02	4.10	4.10	1.50	25.22



More images:





















Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com