

# DIGITUS QSFP+ 40G 5 m DAC cable

DN-81310

EAN 4016032464303



## QSFP+ 40G 5m DAC cable

**Allnet, CISCO, D-Link, Edimax, Etherwan, Fortinet**

The DIGITUS® 40G QSFP+ DAC cables are a high-performance, power-saving close range connection solution. They are compliant with QSFP MSA and IEEE P802.3ba. 4 full-duplex channels are used, each with the capacity to transmit data at speeds of up to 10.3 Gbps, resulting in an aggregated rate of 41.2 Gbps. The DIGITUS® 40G QSFP+DAC cables offer increased port density and cost savings for the entire system.

### High bandwidth without delays or signal loss

- 5 m maximum distance
- 2.125-41.2 Gbps supported data rate
- Supported applications: 12.5G fiber channel, 10G fiber channel, 8G fiber channel, 4G fiber channel and 2G fiber channel

- Compatible brands: Allnet, CISCO, 3COM, D-LINK, Dell, Edimax, Etherwan, ENTERASYS, EXTREME, FINISAR, FORCE 10, Fortinet, HUAWEI, IBM, JUNIPER, LINKSYS, NETGEAR, NORTEL, RIVERSTONE, ZTE, ZYXEL
- DDM / DOM support
- Temperature range: 0 to 70° C
- Connectors: QSFP
- Power: +3.3 V supply voltage
- Power consumption: <1.5W
- 850 nm wavelength multimode fiber

### Attributes

- DDM podrška: Ne

### Package contents

- QSFP+ 40G 5 m DAC cable
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	1.50	48.00	48.00	38.00	87,552.00
Packaging Unit Inside	1	0.01	26.00	26.00	2.00	1,352.00
Packaging Unit Single	1	0.01	26.00	26.00	2.00	1,352.00
Net single without Packaging	0	0.17	11.04	1,835.00	1.34	27.15

## Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

[info@assmann.com](mailto:info@assmann.com)