

DIGITUS USB-C - HDMI Video Adapter Cable, UHD 4K / 30 Hz

DA-70821 EAN 4016032465072





USB-C - HDMI Adapter, 1.8 m 4K/30Hz, black, metal housing

The DIGITUS® USB-C to HDMI adapter cable enables you to connect your notebook or tablet to a monitor, projector or TV device to the USB-C connection. No additional adapters are required. Depending on the source device, this cable supports resolutions of up to 4K / 30 Hz incl. 3D and ARC support. This cable also supports data transfer rates of up to 5 Gbps as well as the USB 3.1 features. You won't need any additional adapters or converters. Simply use the DIGITUS® adapter cable USB-C on HDMI.

Transmits an HDMI signal in UHD 4K via the USB-C interface

- Supported resolutions: 4K /30 Hz (3840 x 2160p), 1080p@120Hz, 720p, 480p
- Data transfer rate: 5 Gbps
- · Chipset: Realtek-RTD2171U
- USB 3.1 Gen 1
- Supports 4K 3D, Full HD 3D HFR
- Supports ARC
- Supports YUV 4:4:4
- Supports HDCP 2.0
- Supports HDMI 1.4b
- Supported color depth: 12 bit
- Supports Consumer Electronic Control (CEC)Supports Lip Sync (audio/video synchronization)
- Supports Multi-Stream audio/video
- Supports 21:9 Cinemascope
- Supports 32 channel audio
- Supports 8-channel LPCM, 192 kHz, 24-bit audio capability
- Supports DTS-HD Master Audio bitstream
- Supports Super Audio CD (DSD)

- · Supports DVD audio
- Supports Blu-ray Disc and HD DVD audio and video
- Supports EDID 2.0 (device recognition)
- Supports DVI Version 1.0
- · Latency: Zero frame delay
- Power consumption: 250 mW max.
- Compatible operating systems: Windows 10/8/8.1/7, MacOS® (OS X), Android, Chromebook Pixel
- Operating humidity: 20% 80% RH
- Operating temperature: -10°C ~ +50°C
- Length: 1.8 m
- Cable sheath: PVC
- Connector housing: Aluminum
- Dimensions: L 46 x W 37.6 x H 13.2 mm
- Weight: 62 g
- Manufacturer's notice:
- Your device equipped with USB-C must support the DisplayPort video mode (DP Alt Mode) in order to be compatible with this adapter/converter.
- The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.

Attributes

- Connector 1: USB C, plug
- Connector 2: HDMI type A, plug
- HDTV Standard: Ultra HD 4K
- USB-C Products: yes

Package contents

• USB-C - HDMI Video Adapter Cable, UHD 4K / 30 Hz

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	7.50	38.10	30.20	31.10	0.00
Packaging Unit Inside	10	0.94	22.50	15.00	15.00	0.00
Packaging Unit Single	1	0.09	22.50	15.00	1.50	506.25
Net single without Packaging	0	58.00	22.00	18.00	0.50	198.00



More images:













Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
 operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com