# DIGITUS Professional 3-in-1 USB charging cable, 1m

**AK-300160-010-S**
**EAN 4016032467113**



**USB charger cable, 1m 3-in-1 cable, nylon braid, black**

The DIGITUS® 3-in-1 charging cable is ideal for charging your portable devices on a power supply unit, PC or other device with a USB-A connection. Use one cable to charge all your devices. The compact dimensions make the cable the ideal companion for home, office or when traveling.

**3-in-1 multi-charging cable for connecting devices with USB-C, micro USB or 8-pin connection to a USB-A connection**

- Supported charging power: 10 W (5 V / 2 A)
- Operating temperature: -10 ~ 50°C
- Operating humidity: 0 - 75%

**Attributes**

- AWG: 30
- Color cable: black
- Connector 1: USB A, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Wire material: CU
- Length: 1 m
- USB-C Products: yes

| **Logistics** | | | | | | |
|---|---|---|---|---|---|---|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 150 | 13.00 | 33.00 | 44.00 | 22.00 | 31.94 |
| Packaging Unit Inside | 5 | 0.43 | 36.00 | 28.00 | 25.00 | 25.20 |
| Packaging Unit Single | 1 | 0.09 | 3.00 | 14.00 | 13.00 | 546.00 |
| Net single without Packaging | 0 | 0.08 | 3.00 | 14.00 | 13.00 | 546.00 |

**More images:**















**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.