

# DIGITUS® USB-C adapter, USB A - USB-C

AK-300524-000-S  
EAN 4016032467410



### USB Type-C adapter, type A to C M/F, 3A, 5GB, 3.0 Version, bl

The DIGITUS® USB Type A to USB-C adapter allows you to use your current USB Type-C devices on an older USB A port. The adapter supports the USB 3.0 specification with data transfers of up to 5Gbps and provides a maximum power of 15 W (3 A). By simply reversing the USB-C connector, you can switch between USB 3.0 and USB 2.0 speeds, provided they are supported by the USB A port. The integrated 56k pull-up resistor protects your devices from damage due to overloading and only supplies as much power as the connected USB-C device requires. Backwards compatible with the USB 2.0 / 1.1 standards, this adapter allows you to use the full bandwidth of previous USB versions.

### Connect USB-C devices with a USB A port - Continue to use your devices with a USB A port

- Adapter: From USB A to USB-C (use USB-C devices on USB A ports)
- SuperSpeed data transfer: 5 Gbit/s (USB 3.0 if supported by USB A)
- USB-C power supply: 3A max. (15 W)
- USB Type-C plug: can be used on both sides, reverse polarity protected
- Integrated 56k pull-up resistor to protect your source devices (notebook, PC)

- Downwards compatible with USB 2.0 / 1.1
- Operating temperature: -15 ~ 50°C
- Operating humidity: -25 ~ 80% RH (non-condensing)
- Storage temperature: -20 ~ 60°C
- Storage humidity: 20% ~ 85% RH (non-condensing)
- Housing material: Aluminum
- Color: Black

### Attributes

- Color cable: black
- Connector 1: USB A, plug
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Length: 0.04 m
- Shielding: Unshielded
- USB-C Products: yes

### Package contents

- 1 x USB Type-C adapter, USB A - USB-C
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	9.00	26.00	38.00	24.00	23.71
Packaging Unit Inside	10	0.09	3.00	20.00	25.00	1.50
Packaging Unit Single	1	0.01	0.70	9.00	20.00	126.00
Net single without Packaging	0	0.01	0.64	1.40	3.80	3.40

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)