

# DIGITUS® Active DisplayPort Adapter / Converter, DP to HDMI

DB-340415-002-S

EAN 4016032468752



## DisplayPort Adapter Cable, Type DP - HDMI A M/F, 0.2m, w/lock, UHD 4K, HDMI 2.0, act, gold, bl

The 4K DisplayPort to HDMI Adapter / Converter (DisplayPort plug to HDMI jack) enables you to reproduce content from your computer or notebook directly onto your TV or other HDMI displays. It supports a UHD resolution of up to 4096 x 2160p. Your images, videos, documents, presentations etc. can be displayed in Ultra HD and optimally presented during meetings or for private use.

**Converts DisplayPort signals to HDMI signals in resolutions of up to UHD 4K**

### Attributes

- AWG: 32
- Blokiranje: Zatvarač na kopču

- DisplayPort standard: DisplayPort 1.2
- Feritni filter: nema
- HDTV-norma: Ultra HD 4K
- Kabel u boji: crni
- Kapice: ukalupljeno
- Konektor 1: DP, utikač
- Konektor 2: HDMI tip A, priključak
- Površina konektora: poniklano
- rezolucija maks.: 4096 x 2160 piksela, 30 Hz
- Duljina: 0.2 m
- AOC - aktivni optički kabel: Ne
- oklop: dvostruki oklop

### Package contents

- 1 x Active DisplayPort Adapter / Converter, DP to HDMI

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	80	7.70	52.00	29.00	39.00	58.81
Packaging Unit Inside	20	1.93	27.00	25.00	17.00	11.48
Packaging Unit Single	1	0.10	23.50	7.50	2.30	405.38
Net single without Packaging	0	0.09	2.46	4.50	1.50	16.61

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)