

DIGITUS Multiple socket outlet with aluminium profile, 4x C13, 4x C14, 2x 16A plug, open end

DN-95423

EAN 4016032473688



1U Aluminum PDU, rackmountable, 4x C13, 4x C19 2x 16A Plug,
250VAC 50/60Hz open end

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	10.50	55.00	46.00	27.00	68.31
Packaging Unit Inside	1	1.05	6.70	50.00	9.10	0.00
Packaging Unit Single	1	1.05	6.70	50.00	9.10	0.00
Net single without Packaging	0	0.77	4.40	48.20	4.40	933,152.00

More images:



Safety notes

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com