

# DIGITUS Gigabit Ethernet PCI Express Network Card 2.5G (4-Speed)

DN-10135

EAN 4016032473978



## 2,5 Gigabit Ethernet PCI Express Card 2.5G Ethernet NIC (CHIPSET:RTL8125B)

This PCIe Gigabit Network Card from DIGITUS® offers you the highest performance for network applications that achieve high data rates with your 10/100/1000/2500 BASE-T ethernet controller. This is ideal for streaming applications with high resolution. Via LAN interfaces (RJ45), it supports the IEEE802.3u specification for fast ethernet and the IEEE802.3ab specification for gigabit ethernet with up to 2.5 Gbps. IEEE802.3x full-duplex flow control is also supported, as well as Wake-on-LAN. The card can be used for slots at full installation height, a low-profile slot bracket is also provided in the scope of delivery for use at half installation height.

### Fast multi-gigabit network connection with up to 2.5 Mbps for your PCI express slot

- Connection: 1 x Gigabit LAN (RJ45)
- Supports 10/100/1000/2500 Mbps networks with automatic recognition
- Conforms with IEEE802.3, IEEE802.3u & IEEE802.3ab specification

- Supports IEEE802.3x full-duplex flow control
- Chipset: Realtek RTL8125B - 2500Base-T Ethernet Controller
- Supports auto MDI/MDIX crossover
- Supports auto MDI/MDIX crossover
- Compatible with PCI Express Specification 2.1
- Supports Wake-on-LAN (WOL)
- Supports IEEE802.1q VLAN tagging
- LED operating display: Active / data traffic / 2.5G data traffic
- Supported operating systems: Windows 7/8/10 (32/64Bit), Windows Server 2008 R2/2012 R2/2016, Linux 4 and higher
- Operating temperature: 5 °C to +50 °C
- Operating humidity: 20% - 80%
- Dimensions (WxDxH): 12 x 9.8 x 2.2 cm
- Weight: 35.2 g

### Package contents

- 1 x Gigabit Ethernet PCI Express Network Card 2.5G
- 1 x Low-profile slot bracket
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	2.00	30.00	46.00	23.00	31.74
Packaging Unit Inside	1	0.10	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.10	14.80	19.00	3.00	843.60
Net single without Packaging	0	35.00	9.80	12.00	2.20	258.72

**More images:**



**Safety notes**

- Switch off the computer completely and disconnect it from the power supply before installing or removing the network card.
- Static discharge can damage the product or the PC. Take measures against static discharge (ESD) when installing the product, e.g. wear an antistatic wrist strap.
- Before installation, touch the metal surface of the PC housing or another grounded object to ground any ESD charge via the housing.
- Avoid using too much force when connecting the product to the PC.
- Please ensure that any cables are connected correctly without overstretching or damaging them.
- Avoid touching the contacts of the product with your fingers to prevent corrosion or static charge.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)