

# DIGITUS Network Rack Unique Series - 800x800 mm (WxD)

DN-31119-B EAN 4016032477815





### 42U network cabinet, Unique, 2053x800x800 mm double perforated doors, no side panels, black

The network cabinets from the Unique series were developed for especially convenient and flexible network cabling. Inlets in the roof and floor equipped with brushes (starting with 26 rack units and a cabinet width of 800 mm), a sliding inlet in the floor structure with  $% \left( 1\right) =\left( 1\right) \left( 1$ foam rubber seal and brush management panels on the back above and below the rear door (starting with 26 rack units) enable versatile use in a wide range of application scenarios. Vertical cable channels with brackets installed next to the profile rails (starting with a cabinet width of 800 mm) round off the design. An offset, removable cover with ventilation slits ensures enhanced air circulation. This features a special design for easy mounting of a fan module. Two pairs of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth is adjustable and they are connected to additional depth bars in the cabinet. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Side walls and doors that can be locked or removed in a modular design improve accessibility. The door hinges can be switched. Furthermore, the cabinets can be completely dismantled if necessary due to their collapsible design.

## The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Steel front and rear door with 70% perforation, double folding
- Locking system with swiveling lever handle on the front and rear door (prepared for profile half cylinder; adapter included)
- · 1-point-locking-mechanism on all doors
- 120° door opening angle on front- and rear doors

- incl. 4 pieces of leveling feet already pre-configured under the rack
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- · Built-in depth support bars for more stability
- Sliding cable entry with rubber sealing on the base
- Special roof construction for fan unit with added lid which can be unmounted
- · Several earthing points for rack components
- Equipment mounting depth min.-max.: 563-743 mm
- Cabinet type: Network cabinet
- Color: black, RAL 9005Depth: 800 mm
- · Front door: Steel door, perforated, double opening
- · Load capacity: 800 kg
- Rear door: Steel door, perforated, double opening
- · Rear door: Steel door, perforated, double opening
- Side panels: Without
- Units: 42
- Width: 800 mm
- IP protection class: without
- Mounted: yes

#### **Package contents**

- 1x Network cabinet
- Installation set (36 x screws, 36 x captive nuts, 36 x washers)
- 1x Adapter for profile half-cylinder
- 4x Grounding cables (incl. nuts and washers)
- 2x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	125.00	85.00	85.00	210.30	1,519,420.00
Packaging Unit Inside	1	125.00	85.00	85.00	210.30	1,519,420.00
Packaging Unit Single	1	125.00	85.00	85.00	210.30	1,519,420.00
Net single without Packaging	0	122.00	80.00	80.00	205.30	1,313,920.00



### More images:

