

DIGITUS® Click & Present Pro - Wireless Collaboration System

DS-55317

EAN 4016032478492



Click & Present Pro - BYOD Collaboration System HDMI, 2x TX, 1x RX

The Wireless Collaboration System from DIGITUS® combines all your devices (notebook, tablet, smartphone) and offers a hardware-based presentation solution for wireless transmission of screen content for meeting/conference rooms. Up to 30 participants can be connected to the receiver. Up to 4 participants can present/collaborate simultaneously in split-screen mode. Notebooks can be connected to the HDMI transmitter and the set can be expanded with additional transmitters (DS-55322). Alternatively, you can stream directly from the notebook (without TX) via wireless screen (Windows)/screen synchronization (macOS) to the receiver. Content from a tablet/smartphone can be conveniently shared via the sharing/cast function (iOS, iPadOS/Android) of your mobile device by connecting your mobile device to the receiver (SSID) via WLAN beforehand. The system setup has been simplified as much as possible - no additional software/apps are required. Increase the efficiency of your meetings, save time and achieve optimized results. Share - Present - Collaborate.

Wireless collaboration/presentation system - presenting from a notebook, tablet or smartphone

- Share, present & collaborate from your notebook, tablet or smartphone
- Easy installation - no software or app required
- Transmission distance: up to 50 m (unrestricted view)
- Simultaneous presentation of up to 4 participants in split-screen mode
- Up to 30 participants (simultaneous connection to the receiver)
- Sharing from notebook via HDMI transmitter (transmitter) or via wireless screen (Windows)/screen synchronization (macOS)
- Sharing from tablet/smartphone via the screen synchronization (iOS, iPadOS/Android) of your mobile device
- Touch Panel Back Control - the touch back function of the receiver unit enables gestures/controls to be sent back wirelessly to a Windows PC using a finger on a large touchscreen
- Integrated whiteboard - the main menu of the receiver has a whiteboard function and, in combination with a touchscreen, enables quick notes to be taken during the meeting or presentation directly on the display
- UHD 4K/60Hz (3840x2160p) on the receiver side - connection of 4K displays
- Supports Windows, macOS, iOS, iPadOS, Android
- Supports HDR (High Dynamic Range)
- BYOD system - Bring Your Own Device
- Set consisting of 2x TX (transmitter) and 1x RX (receiver)
- Expandable with additional HDMI transmitters (transmitters) - DS-55322

- Transmitter connections (transmitter):
- 1x HDMI, plug (Full HD, 1080p) - connection to notebook, video output, cable length: 5 cm
- 1x USB-A, plug - connection on notebook, power supply, cable length: 12 cm
- 1x connection button - Easy sharing
- 1x LED status display
- Receiver connections:
- 1x HDMI, socket (UHD, 4K2K/60Hz) - connection to the output device
- 1x RJ45, socket (Fast Ethernet, 10/100 Mbps) - connection to the network / Internet
- 2x USB-A, socket (USB 2.0) - connection of mouse & keyboard / touch display connection
- 1x USB-C, socket - power supply (10W, 5V/2A)
- 1x LED status display
- 2x radio antenna
- Radio standard: IEEE 802.11 b/g/n/ac, 2.4G/5GHz, 2T2R
- AES 128-bit encryption
- WPA2/WPA-PSK/WPA2-PSK authentication
- Latency: approx. 100 ms (transmitter to receiver transmission)
- Compression: H.264
- Housing: Transmitter - ABS / Receiver - Aluminum
- Dimensions: Transmitter L 8.0 x W 8.0 x H 1.4 cm / Receiver L 8.5 x 10.4 x 2.3 cm
- Color: grey/black
- Notes:
- The transmission distance with limited visibility cannot be determined across the board and depends on the conditions on site
- Walls, glass, etc. shorten the signal coverage or cause signal loss

Attributes

- Distance: 50 m
- KVM: no
- PoE (Power over Ethernet): no

Package contents

- 1x receiver unit
- 2x HDMI transmitter
- 1x USB charging adapter (10W, 5V/2A)
- 1x storage tray for HDMI transmitter
- 2x graphics adapter (HDMI - USB-C)
- 1x USB cable, 1.5 m
- 1x HDMI cable, 1.5 m
- 2x USB adapter (USB-A, socket - USB-C, plug)
- 1x operating instructions

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	8	12.85	43.00	46.00	31.00	61.32
Packaging Unit Inside	1	1.61	19.00	29.00	11.00	6.06
Packaging Unit Single	1	1.61	19.00	29.00	11.00	6.06
Net single without Packaging	0	0.26	8.50	10.40	2.30	203.32

More images:





Safety notes

- Please read these instructions carefully before using the appliance and keep them for future reference.
- For indoor use only.
- Do not use the device in a damp environment or near water.
- Do not expose the product to extremely high or low temperatures, strong light sources or direct sunlight.
- This product is not a toy. Keep it out of the reach of children.
- Do not connect the adapter to the mains until you have made sure that the mains voltage corresponds to the value specified on the rating plate.
- Never connect the power supply unit if it is damaged. In such cases, please contact your supplier.
- Disconnect the AC/DC mains adapter from the power supply if the appliance is not to be used for a longer period of time.
- Never open the product: The appliance may contain parts with lethal voltage. Repairs or maintenance should only be carried out by qualified personnel.
- Improper use, modifications or repairs carried out by the user will invalidate all warranties.
- - We accept no product responsibility for improper or non-intended use of the product.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com