

# DIGITUS Click & Present Pro - Wireless Collaboration System

DS-55317

EAN 4016032478492



## Click & Present Pro - BYOD Collaboration System HDMI, 2x TX, 1x RX

The Wireless Collaboration System from DIGITUS® brings together all your devices (notebook, tablet, smartphone) and offers a hardware-based presentation solution for wireless transfer of screen content for meeting and conference rooms. Up to 30 participants can be connected with the receiver. Up to 4 participants can present/collaborate simultaneously in split screen. Notebooks can be connected with the HDMI transmitter, the set can be extended with additional transmitters (DS-55322). Alternatively, stream directly from the notebook (without TX) via wireless screen (Windows)/screen sync (macOS) to the receiver. Share content conveniently from a tablet/smartphone using the sharing/cast function (iOS, iPadOS/Android) of your mobile device, to do so first connect your mobile device with the receiver (SSID) via WLAN. The configuration of the system has been optimally simplified here - no additional software/apps are required. Increase the efficiency of your meetings, save time and achieve optimal results. Share - Present - Collaborate.

### Wireless collaboration/presentation system - Present from your notebook, tablet or smartphone

- Share, present and collaborate from your notebook, tablet or smartphone
- Easy installation - No software or app required
- Transmission distance: up to 50 m (unrestricted view)
- Present simultaneously from up to 4 participants in split screen
- Up to 30 participants (simultaneous connection to receiver)
- Share notebook via HDMI transmitter or via wireless screen (Windows)/screen sync (macOS)
- Share from a tablet/smartphone using the screen sync (iOS, iPadOS/Android) of your mobile device
- Touch Panel Back Control - the touch back function of the receiver unit allows finger gestures/controls on a large touch screen to be sent back wirelessly to a Windows PC
- Integrated Whiteboard - the main menu of the receiver provides a whiteboard function and in combination with a touchscreen, allows quick notes during the meeting, the presentation directly on the display
- UHD 4K/60Hz (3840x2160p) on the receiver side - Connection of 4K displays
- Supports Windows, macOS, iOS, iPadOS, Android
- Supports HDR (High Dynamic Range)
- BYOD System - Bring Your Own Device
- Set comprising 2x TX (transmitter) and 1x RX (receiver)
- Expandable with additional HDMI transmitters - DS-55322
- Transmitter connections:

- 1x HDMI, plug (Full HD (1080p) - Connection to notebook, video output, cable length: 5 cm
- 1x USB-A, plug - Connection to notebook, power supply, cable length: 12 cm
- 1x Connection button - Easy sharing
- 1x LED status display
- Receiver connections:
- 1x HDMI, jack (UHD, 4K2K/60Hz) - Connection to output device
- 1x RJ45, jack (Fast Ethernet, 10/100 Mbps) - Connection to network/internet
- 2x USB-A, jack (USB 2.0) - Connection of mouse & keyboard / Connection of touch display
- 1x USB-C, jack - Power supply (10W, 5V/2A)
- 1x LED status display
- 2x Radio antennas
- Wireless standard: IEEE 802.11 b/g/n/ac, 2,4G/5GHz, 2T2R
- AES 128 bit encryption
- WPA2/WPA-PSK/WPA2-PSK authentication
- Latency: approx. 100 ms
- Housing: Transmitter - ABS / Receiver - Aluminum
- Dimensions: Transmitter L 8.0 x W 8.0 x H 1.4 cm / Receiver L 8.5 x W 10.4 x H 2.3 cm
- Color: grey/black
- Note:
- The transmission distance with a restricted visual range cannot be determined generally and depends on the specific circumstances where installed
- Walls, glass etc. shorten the signal range or cause signal losses

### Attributes

- Distance: 50 m
- KVM: no
- PoE (Power over Ethernet): no

### Package contents

- 1x Receiver unit
- 2x HDMI transmitter
- 1x USB charging adapter (10W, 5V/2A)
- 1x Storage tray for HDMI transmitter
- 2x Graphics adapter (HDMI - USB-C™)
- 1x USB cable, 1.5 m
- 1x HDMI cable, 1.15 m
- 2x USB adapter (USB-A, jack - USB-C™, plug)
- 1x User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	8	12.85	43.00	46.00	31.00	61,318.00
Packaging Unit Inside	1	1.61	19.00	29.00	11.00	6,061.00
Packaging Unit Single	1	1.61	19.00	29.00	11.00	6,061.00
Net single without Packaging	0	261.00	8.50	10.40	2.30	203.32

**Safety notes**

- Observe all warnings and instructions for the appliance.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Before commissioning, make sure that the device is switched off and is in a safe environment.
- During thunderstorms, damage can occur to connected electrical devices due to overvoltage caused by lightning.
- Do not operate the appliance during thunderstorms.
- Disconnect the appliance from connected electrical devices during thunderstorms.
- Only use the device indoors.
- Return the device to your dealer for repair.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.
- To completely disconnect the system from the power supply, you must unplug the power supply unit from the socket. You can disconnect the device from the power supply via the power supply unit.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)