

4K HDMI Splitter, 1x16

DS-45328

EAN 4016032479994



4K HDMI Splitter, 1x16 4K/60Hz, 18Gbps, HDR, Downscaling, EDID

The DIGITUS® 4K HDMI Splitter, 1x16 distributes an AV signal onto 16 screens in UHD resolution (4K/60Hz). Thanks to the down-scaling function, no screen will remain black if for example a 4K signal needs to be output simultaneously on 4K and Full HD monitors. The splitter also offers the option of EDID management; different modes can be individually configured via the changeover switch.

Distributes an HDMI signal onto 16 screens in UHD resolution (4K/60Hz)

- Supports 4K2K/60Hz (HDR, 4:4:4)
- Video bandwidth: 18 Gbps
- Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible
- EDID management changeover switch
- HDMI 2.0
- HDCP 2.2 / 1.4
- Supports High Dynamic Range (HDR)
- Supports Deep Color (36-bit), 12 per channel
- Supports compressed audio formats such as LPCM
- Supports uncompressed audio formats such as DTS, Dolby Digital
- 17x Status LED
- Input:
 - 1x HDMI jack (4K/60Hz)
- Output:
 - 16x HDMI jack (4K/60Hz)
- Operating temperature: 0-70°
- Power consumption: approx. 12W
- Housing: Metal
- Dimensions: L 10.9 x W 25.7 x H 2.3 cm
- Color: black
- Supports 4K2K/60Hz (HDR, 4:4:4), Video bandwidth: 18 Gbps, Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible, EDID management changeover switch, HDMI 2.0, HDCP 2.2 / 1.4, Supports High Dynamic Range (HDR), Supports Deep Color (36-bit), 12 per channel, Supports compressed audio formats such as LPCM, Supports uncompressed

audio formats such as DTS, Dolby Digital, 17x Status LED, Input: 1x HDMI jack (4K/60Hz), Output: 16x HDMI jack (4K/60Hz), Operating temperature: 0-70°, Power consumption: approx. 12W, Housing: Metal, Dimensions: L 10.9 x W 25.7 x H 2.3 cm, Color: black,,

- Supports 4K2K/60Hz (HDR, 4:4:4), Video bandwidth: 18 Gbps, Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible, EDID management changeover switch, HDMI 2.0, HDCP 2.2 / 1.4, Supports High Dynamic Range (HDR), Supports Deep Color (36-bit), 12 per channel, Supports compressed audio formats such as LPCM, Supports uncompressed audio formats such as DTS, Dolby Digital, 17x Status LED, Input: 1x HDMI jack (4K/60Hz), Output: 16x HDMI jack (4K/60Hz), Operating temperature: 0-70°, Power consumption: approx. 12W, Housing: Metal, Dimensions: L 10.9 x W 25.7 x H 2.3 cm, Color: black,,
- Supports 4K2K/60Hz (HDR, 4:4:4), Video bandwidth: 18 Gbps, Down-scaling function (4K -> 1080p) - Mixed operation of Full HD + 4K screen possible, EDID management changeover switch, HDMI 2.0, HDCP 2.2 / 1.4, Supports High Dynamic Range (HDR), Supports Deep Color (36-bit), 12 per channel, Supports compressed audio formats such as LPCM, Supports uncompressed audio formats such as DTS, Dolby Digital, 17x Status LED, Input: 1x HDMI jack (4K/60Hz), Output: 16x HDMI jack (4K/60Hz), Operating temperature: 0-70°, Power consumption: approx. 12W, Housing: Metal, Dimensions: L 10.9 x W 25.7 x H 2.3 cm, Color: black,,

Package contents

- 1x HDMI splitter
- 1x Power adapter (12V/2A, 1.15 m)
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	22.00	58.50	60.00	26.00	91.26
Packaging Unit Inside	1	1.10	23.80	29.20	5.50	3,822.28
Packaging Unit Single	1	1.10	23.80	29.20	5.50	3,822.28
Net single without Packaging	0	0.73	11.00	25.70	2.30	650.21

More images:

