

DIGITUS® 8K Mini DisplayPort Adapter Cable, Mini DP - HDMI Type A

DB-340109-010-S
EAN 4016032484219



DisplayPort Adapter Cable, Type mini-DP - HDMI M/M, 1.0m, Alu Housing, UHD 8K, DP 1.4, bl

This digital HD high-performance audio/video cable is used to connect PCs or notebooks with Mini DisplayPort interface to monitors with HDMI interface.

Avoid adapters with a Plug and Play cable adapter that does not require external power supply

- Supports HDMI 2.1 and mini-DisplayPort 1.4 characteristics
- Supports up to 8K with 60Hz
- Supports 8K 3D with a resolution of 1080p
- Support of digital audio transmission in stereo
- Supports HDCP and DPCP
- Hood: Aluminum housing
- AOC - Active Optic Cable: no

Attributes

- AWG: 32
- Color cable: black
- Connector 1: Mini DP, plug
- Connector 2: DP, plug
- Connector surface: gold-plated
- DisplayPort standard: DisplayPort 1.4
- HDTV Standard: Ultra HD 8K
- Hoods: Aluminum
- Interlock: none
- Length: 1 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Package contents

- 1x 8K Mini DisplayPort Adapter Cable, Mini DP - HDMI Type A, 1 m

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 120 | 6.40 | 49.00 | 52.00 | 25.00 | 63.70 |
| Packaging Unit Inside | 1 | 0.05 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.05 | 2.30 | 7.50 | 23.50 | 405.38 |
| Net single without Packaging | 0 | 0.03 | 2.00 | 7.00 | 21.50 | 301.00 |

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com