

DIGITUS® 4K USB Adapter, USB-C plug to HDMI-A jack

AK-300450-000-S
EAN 4016032486169



USB-Type-C-Adapter,USB-C to HDMI Type-A, 4K@30HZ Aluminum housing, black

The DIGITUS® 4K USB-C Adapter enables you to connect your notebook or tablet to a monitor, projector or TV device to the USB-C connection. No additional adapters are required. Depending on the source device, this adapter supports resolutions of up to 4K / 3840 x 2160 with a display refresh rate of 30 Hz. incl. 3D and ARC support.

Converts audio/video signals to HDMI signal in UHD 4K via the USB-C interface.

- Transmits an HDMI signal in UHD 4K via the USB-C interface
- Supports 4K / 30 Hz
- Plug and Play - no driver installation required
- Elegant aluminum housing
- Your device equipped with USB-C must support the DisplayPort video mode (DP Alt Mode) in order to be compatible with this adapter/converter.

- The video output capabilities depend on your notebook's graphic card and the connected monitor. Some screens also limit the available resolution.

Attributes

- Color cable: black
- Connector 2: HDMI type A, jack
- Connector surface: gold-plated
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Resolution max.: 3840 x 2160 Pixel, 30Hz
- Length: 0.05 m
- AOC - Active Optical Cable: no

Package contents

- 4K USB Adapter, USB-C plug to HDMI-A jack

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	50	0.90	18.00	24.00	31.00	13.39
Packaging Unit Inside	25	0.45	16.00	11.00	29.00	5.10
Packaging Unit Single	1	0.02	3.00	5.50	10.00	165.00
Net single without Packaging	0	0.01	0.00	0.00	0.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com