

DIGITUS Label Printer 200dpi

DA-81020
EAN 4016032487029



Bar Code Label Printer, 200dpi Thermal Direct/Transfer, USB, LAN, Serial

The DIGITUS Label Printer is a high quality thermal printer for individual and business label printing that fits comfortably on the desktop. The printer offers a resolution of 200 DPI, a print speed of up to 127mm/s and a USB 2.0/RS-232/Ethernet interface. The printer is ideal for product labeling, shipping labels, retail and other labeling applications. The label roll is located directly in the housing.

The label printer is versatile and ideal for creating shipping labels and barcode labels in the office and at home

- Resolution 203 DPI
- Printing method thermal transfer / direct thermal
- Max. Print speed: 127 mm (5") / s Max.
- Max. Print width/length: 108mm (4.25") / 2286mm (90")
- Print media: continuous, gap, black mark, fanfold and perforation
- Media width/thickness: 25.4-118mm (1.0-4.6") / 0.06-0.254mm (2.36-10mil)
- Media core diameter 25.4-76.2mm (1-3")
- Label length 10-2286mm (0.39-90")
- Label roll capacity 127mm (5") (outer diameter)
- Ribbon capacity Max: 300m
- Ribbon width: 110mm
- Ribbon core inner diameter: 25.4mm (1")
- Performance Features: Processor 32-bit CPU


- Memory 4MB flash memory, 8MB SDRAM, SD card reader for flash memory expansion, up to 4GB
- Interface: USB2.0/Serial/Ethernet
- Internal fonts: 8 alphanumeric bitmap fonts, Windows fonts can be downloaded from software.
- 1D barcode: Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
- 2D barcode PDF-417, Maxicode, DataMatrix, QR code, Aztec
- Rotation: 0°, 90°, 180°, 270°
- Emulation: TSPL, EPL, ZPL, DPL
- Dimensions 302,5mm (D) x 234mm (W) x 194,8mm (H)
- Weight 2.6kg

Package contents

- 1x Label Printer
- 1x Power supply
- 1x USB cable
- 1x Test label paper
- 2x Label role receptacle
- 1x Cardboard sleeve
- 1x Ribbon
- 1x Ribbon recycling roll
- 2x Ribbon screw
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	4	18.00	59.00	43.00	64.00	162.37
Packaging Unit Inside	1	4.50	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.50	40.50	27.50	29.00	0.00
Net single without Packaging	0	2.60	30.30	23.40	19.50	0.00

More images:



Safety notes

- Do NOT look directly into the LED light.
- Do not look at the light source either directly or using optical aids.
- Do NOT expose the reader to flammable substances.
- Under no circumstances should you attempt to carry out unauthorized repairs to the installed components.
- A socket outlet for the AC power supply should be available and easily accessible near the device. Ensure a stable power supply so that the reader and peripheral devices function correctly.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com