

DIGITUS® Industrial 8+4 port Gigabit Ethernet PoE switch

DN-651153

EAN 4016032490494



Industrial 8+4-Port Gigabit Ethernet PoE Switch 8 x GE RJ45 + 2 SFP+ Port, PoE

The DN-651153 is a robust 8+4 port Industrial Gigabit Ethernet PoE switch for harsh environments. With non-blocking wire-speed performance, it offers 8x 10/100/1000 BASE-TX RJ45 (up to 30 W PoE each) + 4 x 1000 Base-Fx ports. The IP40 enclosure with redundant power supply is ideal for monitoring, control management and wireless services at -40 to 80°C.

8x PoE 10/100/1000 BASE-TX RJ45 + 4 x 1000Base-Fx ports. The IP40 enclosure with redundant power supply is ideal for monitoring, control management and wireless services at -40 to 80°C.

- Supports IEEE802.3x flow control, and backpressure
- Supports store-and-forward technology for optimized data transmission
- Automatic speed and half/full duplex detection/adjustment
- 8 port PoE with up to 30 W
- Bandwidth: 52 Gbps
- Packet buffer: 4.1 Mbit
- Packet forwarding size: 38.7 Mbps
- Size of the MAC address table: 8K
- Jumbo frame rate: 9000 byte
- ESD protection: 6 kV (DC)
- EFT protection: 6 kV (DC)
- Metal housing, IP40
- 4 kV lightning protection and surge protection

- Redundant power supply with reverse polarity protection function
- Power supply: 48 to 57 V
- Power consumption: < 10 W
- Removable terminal connection
- Protection class: IP40
- Dimensions: 143.7 x 125 x 47.7 mm
- Weight: 0.76 kg
- Operating temperature: -40 to 80 °C
- Storage temperature: -40 to 80 °C
- Humidity: 5% to 95% (non-condensing)
- MTBF: 300,000
- Total PoE budget: 200 W

Attributes

- Broj priključaka: 8
- PoE norma: IEEE802.3af (PoE)
- Ethernet brzina: Gigabit
- Industrijska uporaba: Da
- Broj priključaka (Uplink): 4
- PoE (napajanje preko Ethernet): Da
- Prikladno za vanjsku primjenu: Ne
- Upravljačno: Ne
- Veza uzlaznog (Uplink) priključka: SFP
- VLAN: Ne
- Zaštita od vandalizma: Ne

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 20 | 15.00 | 34.30 | 35.00 | 44.50 | 53,422.20 |
| Packaging Unit Inside | 1 | 0.75 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.75 | 6.60 | 15.80 | 21.30 | 2,221.16 |
| Net single without Packaging | 0 | 0.67 | 4.77 | 12.50 | 14.37 | 856.81 |

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com