

DIGITUS® FTTH Enclosure with 2 x LC/APC DX couplers

DN-931096

EAN 4016032494676



FTTH Enclosure, with 2x LC(APC) DX adapter Surface mount

The Fibre wall outlet is designed to be used as an optical telecommunications outlet. It is an ultra compact enclosure for managing up to 4 fibres within the property and can be easily wall mounted providing the connection point for upto 4 end devices. It is pre-assembled with 2 x LC/APC Duplex couplers and offers entry points at the rear, bottom and top for flexible cable entries according to requirement. It efficiently brings together the possibility of fiber splices, terminations, storage and connections in a minimal space. Also the screw holes on the rear allow for easy installation and positioning maintaining the outlet flush to the wall.

FTTH wall outlet designed minimalistically for distribution of up to 4 fibers. The compact protective housing is perfect in FTTH and office premise cabling for fiber splices, terminations and connections.

- Design : Wall outlet
- Mounting style : Surface mount

- Transmission technology : Fiber optic
- Integrated splice cassette
- Type of fiber : Singlemode
- Connector interface : LC Duplex
- Connector type : LC/APC
- Number of ports interface : 2
- Number of equipped ports interface : 2
- Cable access/outlet : Rear, top, bottom
- Housing material: PC + ABS
- Protection type: IP45
- Operating temperature: -40°C ~ +85°C
- Color : Pure white
- Dimensions (LxWxH): 104 x 80 x 23 mm
- Weight: 0.07 kg

Package contents

- FTTH enclosure with 2 x LC/APC DX couplers

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	18.00	50.00	50.00	28.00	70,000.00
Packaging Unit Inside	1	0.09	3.00	9.00	11.50	310.50
Packaging Unit Single	1	0.09	3.00	9.00	11.50	310.50
Net single without Packaging	0	0.00	0.00	0.00	0.00	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com