

# DIGITUS® USB silicone cable, USB 3.2 Gen2, USB 10Gbps, 0.5m, black

AK-300342-005-S  
EAN 4016032496069



## USB Silicone connection cable, USB-C - USB-C 0.5m, USB 3.2 Gen2, 10G, 4K, 100W, black

Reliable and easy connection to your USB-C devices with your PC thanks to the soft and flexible silicone cable. Data transfer rates of 10 Gbits/s for synchronization and data transfer, a 4K screen resolution and a power delivery specification of 100W for charging are possible with this high-quality cable.

**Fast charging and synchronization with the high-quality and soft silicone connection cable. 4K video transmission is possible with the USB version USB 3.2 Gen2**

- Supports data transfer rates of 10 Gbps
- Backwards compatible with USB 3.1, USB 3.0, USB 2.0 and USB 1.1
- Supports the USB power delivery function with 20V, 5A and 100W
- Supports 4K (3840x2160) @60Hz

- Durable cable with a service life of up to 10,000 bends (based on internal tests)
- Type C plug can be used on both sides

### Attributes

- AWG: 31
- Feritni filter: nema
- Kabel u boji: crni
- Konektor 1: USB C, utikač
- Konektor 2: USB C, utikač
- Površina konektora: poniklano
- USB sukladnost: USB 3.0 / 3.1
- Duljina: 0.5 m
- oklop: trostruki oklop

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	200	6.00	21.00	32.00	50.00	33,600.00
Packaging Unit Inside	10	0.30	2.20	24.00	30.00	1,584.00
Packaging Unit Single	1	0.03	0.68	21.00	11.50	163.01
Net single without Packaging	0	0.02	0.58	12.00	10.00	69.60

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)