

# DIGITUS® Aluminum socket strip, 7-way with circuit breaker

DN-95439

EAN 4016032501664



## 1U Alu PDU, rackmount., 7x safety outlet 16A, 4000W, 250VAC 50/60Hz, 1x circuit breaker

Order and flexibility in the server rack with the DIGITUS® Professional socket strips. Plug your devices centrally into the 45° arranged safety sockets, blocking or covering the adjacent sockets is a thing of the past. Perfectly suited for 482.6 mm (19") server and network cabinets, the socket strips offer well thought-out features. With the supplied mounting brackets, the socket strip fits easily into the 482.6 mm (19") grid of your network cabinet and makes a neat impression. Designed for horizontal mounting, vertical mounting is also possible. The supply cables to the socket strip are protected by the integrated circuit breaker, which prevents overloading of the incoming cabling.

### Safety, order and flexibility in the server rack - the DIGITUS® 482.6 mm (19") socket strips

- 7 socket outlets with earthing contact 250VAC 50/60Hz / 16A / 4000 W
- Circuit breaker: 16 A, type C
- Miniature circuit-breaker: Short-circuit breaking capacity (Icn & Ics) - 6000A
- 45° arrangement of the sockets: No blocking or covering of the adjacent sockets
- Mounting bracket for 482.6 mm (19") mounting

- High-quality aluminum housing
- Child safety lock: plastic covers seal the contacts of the socket outlet
- Input voltage: 230 V AC
- Frequencies: 50 ~ 60 Hz
- Mains cable with earthing contact plug: 1.8 m, 3G x 1.5 mm²
- Dimensions: L 48.1 x W 4.5 x H 8.3 cm
- Weight: 800 g
- Color: Silver/Black

### Attributes

- Dodatne mogućnosti: Rastavljač strujnog kruga
- Izlazni priključci: CEE 7/3
- Mjerenje: PDU mjerenje
- Struja: 16 A
- Ugrađivanje: Stalak 1U
- Ulazni utikač: CEE7/7
- Volti: 230 V
- Inčni faktor oblika (IEC 60297): 482,6 mm (19")

### Package contents

- 1 x 7-socket power strip 482.6 mm (19") aluminum, 1 U with circuit breaker
- 2 x variable mounting brackets 482.6 mm (19")
- 1 x operating instructions

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 10           | 11.25       | 35.00      | 55.00      | 29.50       | 56,787.50 |
| Packaging Unit Inside        | 1            | 1.13        | 7.00       | 14.50      | 55.00       | 5,582.50  |
| Packaging Unit Single        | 1            | 1.13        | 7.00       | 14.50      | 55.00       | 5,582.50  |
| Net single without Packaging | 0            | 0.85        | 4.50       | 4.50       | 48.26       | 977.27    |

**More images:**



**Safety notes**

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)