

DIGITUS® USB-A - RJ45 Ethernet cable, 1Gbit/s, 2m

AK-300600-020-S

EAN 4016032501978



USB-A - RJ45 CAT 6A S/FTP Cable, 1 Gbit/s, 2m USB 3.2 Gen1, LSZH Jacket

With the Digitus USB 3.2 Gen1 - RJ45 Ethernet cable, you can easily connect your USB-A enabled device to a wired network and benefit from a stable and fast Gigabit Ethernet connection. The cable replaces the conventional Ethernet adapter and offers a space-saving, compact solution without additional devices. Ideal for laptops and peripheral devices that do not have an integrated LAN connection. It provides fast and reliable connections to the Internet - perfect for video streaming, online meetings or data-intensive applications. Thanks to the support of Wake-On-LAN and "RealWoW!" (Wake-On-WAN) technology, you can even activate your device remotely. The safe LSZH (Low Smoke Zero Halogen) casing minimizes smoke development and toxic fumes in the event of fire - ideal for installations in public or sensitive areas. The plug-and-play installation enables immediate use, and the cable is fully compatible with macOS and Windows - without any additional drivers or external power supply. A versatile and secure solution for any setup!

Fast, reliable network connection via USB-A - ideal for modern devices without an Ethernet port. Experience gigabit speed and seamless plug-and-play installation.

- Speed: 10/100/1000 Mbps (supports Gigabit Ethernet)
- CAT version: CAT 6A S/FTP
- USB version: USB 3.2 Gen1, downward compatible
- Compatibility exists with the following operating systems up to their current versions: Windows 7 or higher, macOS 12 or higher, ChromeOS 116.0.5845.120 or higher, Linux 22.04 LTS or higher
- Plug-and-play: without driver installation
- Supported: Wake-On-LAN, RealWoW! (Wake-On-WAN) for remote access
- Power: USB-powered, no external power supply required
- Aluminum housing for long-lasting use
- Outer diameter: 6.2 mm, AWG 26


- Chipset: RTL8153E
- Advanced functions:
 - Pair-swap, polarity and distortion correction: Improves signal quality and ensures a stable connection, even in difficult network conditions
 - Crossover detection and correction: Automatic correction of cable twists ensures reliable communication without connection problems
 - Full-duplex flow control in accordance with IEEE 802.3x: Enables bidirectional data transmission simultaneously for efficient network communication
 - On-chip buffer support: Temporary storage of data packets ensures stable and continuous data transmission
- Energy efficiency & standards:
 - IEEE 802.1P Layer 2 Priority Encoding: Supports network prioritization to optimize performance during simultaneous use.
 - IEEE 802.1Q VLAN tagging: Enables network segmentation and improved data management through VLAN support.
 - IEEE 802.3az-2010 (EEE = Energy Efficient Ethernet): Supports energy-efficient Ethernet connections to reduce power consumption during low activity.
 - Power save mode: Supports power save mode during power off or link power down for even more energy efficiency.

Attributes

- AWG: 26
- Color cable: black
- Connector 1: USB A, plug
- Connector 2: RJ45, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Category: CAT 6A
- Length: 2 m
- Shielding: S-FTP, pairs in metal foil and braid shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	6.34	32.00	50.00	21.00	33,600.00
Packaging Unit Inside	10	1.06	40.00	35.00	2.00	2,800.00
Packaging Unit Single	1	0.11	25.00	14.00	2.00	700.00
Net single without Packaging	0	0.08	18.00	9.00	2.00	324.00

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com