

DIGITUS USB-C 3.0 Dual HDMI KVM Switch, 2-port, 4K60Hz, Core Line

DS-12856

EAN 4016032506577



KVM Switch, 2x2 HDMI, 4K@60Hz 3x USB3.0, 1x USB C, Core Line

DIGITUS USB-C 3.0 Dual HDMI KVM Switch, 2-port, 4K60Hz, Core Line Two computers, two monitors - complete control via a single keyboard and mouse combination and razor-sharp 4K image quality. The DIGITUS® USB-C 3.0 Dual HDMI KVM Switch from the Core Line enables simultaneous control of two HDMI™-capable computers with dual display output - ideal for workstations with two monitors.

Switching between the systems is effortless with the push of a button or via the supplied wired remote control. In addition to support for up to 4K@60Hz (YUV 4:4:4), HDR and HDCP, the switch also offers extended connection options for USB peripherals. Three USB-A 3.0 ports and one USB-C 3.0 port enable the shared use of storage devices, printers or input devices with data rates of up to 5 Gbit/s. Note: When using external hard disks or SSDs with higher power consumption, it is recommended to use an additional 5V/2A power adapter (not included). An integrated 3.5 mm audio output provides clear stereo sound. Power is supplied via USB-C; an optional connection for an external power supply is available for devices with higher power requirements.

Switch seamlessly between two devices without having to reconnect - 4K@60Hz, USB 3.0, audio and compact design ensure efficient working and a tidy desk environment.

- Inputs: 2x HDMI™ (for two devices), 2x USB-C 3.0 (data/control)

- Outputs: 2x HDMI™ (single display), 3x USB-A 3.0 (up to 5 Gbps), 1x USB-C 3.0 (up to 5 Gbps), 1x audio 3.5 mm
- Control :Switching via button on the appliance or via remote control (1.5 m, magnetic)
- Video resolution : Up to 4K@60Hz (YUV 4:4:4), HDR support, 3D compatible
- Audio : Stereo (3.5 mm), DTS, Dolby Digital, TrueHD
- Video bandwidth : Up to 6.0 Gbit/s per channel / 18 Gbit/s total
- Supported formats : LPCM, DTS, Dolby Digital, HDCP 1.4 / 2.2
- Housing material :Aluminum housing for stability and cooling
- Dimensions (L x W x H): 135 x 60 x 30 mm
- Weight :227 g
- Power supply : Via USB-C (DC 5V), optional 5V/2A power supply recommended for power-intensive USB devices

Attributes

- Interface: HDMI
- Number of ports: 2

Package contents

- 1x USB-C 3.0 Dual HDMI™ KVM Switch, 2-port
- 2x USB-A to USB-C 3.0 data cable (1.5 m)
- 1x USB-A to USB-C power cable (1 m)
- 1x remote control with magnetic base (1.5 m)
- 1x quick start guide

More images:





Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.