

# DIGITUS® CAT 6, modular couplers, shielded

AT-AG 8/8 C6S

EAN 4016032229032



### Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0

- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

#### Attributes

- Category: CAT 6

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
<b>Packaging Unit Carton</b>	1000	11.67	30.00	55.00	27.00	44,550.00
<b>Packaging Unit Inside</b>	100	1.17	14.00	25.50	10.50	3,748.50
<b>Packaging Unit Single</b>	1	0.01	8.00	10.00	1.80	144.00
<b>Net single without Packaging</b>	1	0.01	8.00	10.00	1.80	144.00

### Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)