# DIGITUS® Fiber Optic Multimode Patch Cord, OM 3, ST / ST

**DK-2511-10/3**

**EAN 4016032248323**




**FO patch cord, duplex, ST to ST MM OM3 50/125 µ, 10m**

FO patch cord, duplex, ST to ST,MM OM3 50/125 µ, 10m

**Future-oriented standards and high-end quality for your network.**

- Duplex cable
- LSOH
- Connector with ceramic ferrule
- Cable diameter 2 mm
- Single packed with test-report

**Attributes**

- Assortment: Fiber Optic Patch Cables


- Boot: two-color
- Cable diameter: 2 mm
- Cable type: I-VH 2G50/125µ
- Color cable: aqua
- Connector 1: ST
- Connector 2: ST
- Fiber class: OM3
- Fiber diameter: 50/125µ
- Mode: Multimode
- Packaging: DIGITUS Polybag
- Length: 10 m

**Logistics**

| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
|---|---|---|---|---|---|---|
| **Packaging Unit Carton** | 40 | 7.15 | 41.00 | 41.00 | 28.00 | 47,068.00 |
| **Packaging Unit Inside** | 5 | 0.89 | 19.00 | 19.00 | 12.00 | 4,332.00 |
| **Packaging Unit Single** | 1 | 0.18 | 17.00 | 17.00 | 2.40 | 693.60 |
| **Net single without Packaging** | 1 | 0.17 | 17.00 | 17.00 | 2.40 | 693.60 |


Druckfehler, Irrtümer und technische Änderungen sind vorbehalten. | Printing errors, falsities and technical changes remain reserved.

**More images:**







| | | | | |
|---|---|---|---|---|
| Part No. | DK-2511-10/3 | | | |
| Lenght | 10 m | | | |
| Cable Type | Duplex MM 50/125 | | OM3 LSZH | |
| | END A | | END B | |
| Connector Type | ST | | ST | |
| Insertion Loss (dB) | 0.09 | 0.05 | 0.16 | 0.15 |
| Return Loss (dB) | 39.0 | 39.7 | 36.5 | 36.9 |
| Q.C. | PASS | | | |

**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
https://www.assmann.com
info@assmann.com