

DIGITUS CAT 5e, Class D, RJ45 Modular Coupler

DN-93901**EAN 4016032266488****CAT 5e Modular Coupler, shielded RJ45 to RJ45**

The modular CAT5e Class D coupler from DIGITUS® consists of two shielded RJ45 female ports. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ

- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1000	9.00	51.00	27.00	25.00	34,425.00
Packaging Unit Inside	50	0.45	17.00	8.00	17.00	2,312.00
Packaging Unit Single	1	0.01	1.20	6.00	9.00	64.80
Net single without Packaging	1	0.00	1.20	6.00	9.00	64.80

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com