

DIGITUS® Mains cable extension

AK-440201-018-S

EAN 4016032311898



Power Cord extension cable, C14 - C13 M/F, 1.8m, H05VV-F3G 0.75qmm, bl

This power cable is used to connect the PC power supply unit to the monitor, reducing the need for a power socket. It can also be used as an extension cable.

Complies with European directives

- VDE tested

Attributes

- Assortment: Device Connection Cables
- Cable standard: H05 VV F3G

- Color cable: black
- Color connector: black
- Connector 1: IEC C14, plug
- Connector 2: IEC C13, jack
- Connector surface: nickel-plated
- Current load capacity: 250V/10A
- Hoods: molded
- Lead cross-section: 0.75qmm
- Wire material: CU
- Length: 1.8 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	70	13.53	55.00	36.50	20.00	40,150.00
Packaging Unit Inside	10	1.93	17.00	34.00	7.00	4,046.00
Packaging Unit Single	1	0.19	5.50	13.00	18.00	1,287.00
Net single without Packaging	1	0.19	5.50	13.00	18.00	1,287.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com