

DIGITUS® Bluetooth® 4.0 Tiny USB Adapter

DN-30210-1

EAN 4016032325062



Bluetooth V4.0 + EDR Tiny USB Adapter, Class 2 CSR chipset

Bluetooth V4.0 + EDR Tiny USB Adapter, Class 2, CSR chipset

- Dual-mode support, Bluetooth® 4.0 and Bluetooth® 3.0
- Ultra low power consumption
- CSR Bluetooth® Chipset
- Operation distance up to 10 m
- Support profile: A2DP, AVRCP, Serial Port, Object Push, File Transfer, LAN Access, Personal Area Network, Audio Gateway, Headset HID, Keyboard, Mouse, HCRP (Printer Cable Replacement)
- Communicates with all standard Bluetooth® devices
- System Requirements: PC with USB 1.1 / USB 2.0 / USB 3.0, Microsoft Windows 7, 8, Vista, XP support
- Full-speed USB 2.0 interface

- LED indication: Power on, Linking, Standby
- 2.402-2.48 GHz ISM Band
- Operating humidity: RH45% ~ RH85%
- Operating temperature: -10°C ~ 50°C
- Storage temperature: -20°C ~ 60°C
- Bluetooth® v. 4.0 specification compliant
- Supports Windows 10, 8, 7, Vista and XP
- Supports BLE (Bluetooth® Low Energy)
- Plug & Play installation – no additional software required
- Dimension: 23 x 14.2 x 4.5 mm
- Weight: 2.4 g

Package contents

- Bluetooth® USB Adapter

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	200	5.35	45.50	28.50	30.00	38,902.50
Packaging Unit Inside	50	1.34	27.00	22.00	13.50	8,019.00
Packaging Unit Single	1	0.03	1.30	10.30	12.30	164.70
Net single without Packaging	1	0.02	1.30	10.30	12.30	164.70

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com