

# DIGITUS® LC Keystone Adapter for Patch Panel

DN-BLIND-LC

EAN 4016032342274



### LC keystone frame for patch panel color white

The DIGITUS® Snap-in adapters for Patch Panel offer you the easiest solution to expand empty fields of your Patch Panel or to cover them. The LC Keystone frames contains a slot in each case for LC plugs and are therefore optimal to optimize the cabling of your Patch Panel. All

DIGITUS® Snap-in adapters are available in the colors grey or black. Also available are special LC couplers without flanks.

### The fiber optic solution for your modular Patch Panels

- Keystone frame for LC couplers
- Color: white

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	5000	9.50	50.00	33.00	35.00	57,750.00
Packaging Unit Inside	100	0.19	17.00	10.00	5.00	850.00
Packaging Unit Single	1	0.00	1.00	1.00	1.00	1.00
Net single without Packaging	1	0.00	1.00	1.00	1.00	1.00

### More images:



### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage

- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)